

Engineer Report CP009


Cutblocks: TS2


Prepared By: Chris Law, RFT


Date: June 30, 2016

Contents

Appendix 1: CP 009 Overview Map		3
Appendix 2: Harvest Map and Instructions		<u>4</u>
Appendix 3: Road Construction Map and Instructions		6
Appendix 4: Road Designs		8
Appendix 5: Site Plans and Site Plan maps		39
Appendix 6: Deflection Line Package	48	
Appendix 7: Safety Highlights	61	
Appendix 8: Wet Weather Shutdown Guidelines		63
Appendix 9: Cruise Report		66
Appendix 10: Terrains Stability Assessment		119







HARVESTING INSTUCTIONS – OPENING# TS2

ACCESS ROAD: TA568 TIMBERMARK: K2D/009 CUTTING PERMIT: 009

EMPLOYEE REQUIREMENTS

1) All employees, supervisors and contractors associated with this Logging Plan approval shall be fully advised of its contents and requirements.

2) All litter including cable, oil buckets, grease tubes, newspapers and lunch garbage is to be removed from the site and disposed of appropriately.

WATER QUALITY

1) The overall objective of this cutblock is timber harvesting without impacting the water quality.

2) All ditches and culverts must remain as free flowing as possible through all phases of harvesting.

3) Cutblock TS2 is within Rainfall Shutdown Area "5"

Shutdown Criteria: Activities must shut down if: The total rainfall reaches 72 mm in 24 hours. Onsite rain gages should be used and monitored daily.

Start-Up Criteria: Activities may start-up when: The total rainfall is equal to or less than 30 mm in 24 hours. Refer to the Return to work guide in the tender document for more information.

1) Invasive Plants: Broom occurs along sections of TA568. Follow FSP measures for invasive plants. Cut and remove plants in association with road reactivation, clean machinery as required. Monitor and treat broom and other invasive species during early establishment. Grass seed exposed soil on or adjacent to roads, trails, and landing sites as soon as possible following harvest.

FIRST NATIONS

1) This cutblock is in the Hupacusath traditional territory. An information sharing process was done with the Hupacasath and Tsheshaht First Nations. If any additional potential culturally modified tree (CMT) (whether live or dead and standing or fallen) or any other cultural feature is encountered within the opening during any harvesting phase, operations will cease in the immediate vicinity of the CMT or cultural feature. Hupacusath and Tseshaht First Nations are to be notified immediately upon discovery of any potential CMT or cultural feature.

FALLING of SNAGS and DANGER TREES

1) In accordance with the WCB Regulations, snags and danger trees within the cutblock and outside the cutblock boundaries for a distance of not more than 50 meters that endanger workers are approved for falling under the logging plan for this cutblock. Danger trees and snags outside this 50 meter hazard area that are required to be felled should be recorded on a map for future reference. Sanitation falling will proceed if the occasional stem is required to be removed along the cutblock boundary. The Ministry of Forests will be notified if danger trees and/or snags are identified in groups and removal will result in the cutblock boundary being substantially impacted. Snags and danger trees meeting utilization specifications will be recovered.

2) If a bear den or raptor nest is encountered during falling operations, the tree will be reserved from falling along with a protection patch of timber surrounding it. AVCF is to be notified immediately. If the bear den tree is partially cut operations will proceed in conformance with WCB regulations.

3) Wildlife tree patches and OGMA's have been established, and are marked on the 1:5000 map. Any danger trees felled within the WTP or OGMA will be left as Coarse Woody Debris.

CUTBLOCK BOUNDARY TREATMENTS

1) All marked boundary trees except snags and danger trees must remain standing during and after the completion of harvesting. Trees adjacent to second growth edges that cannot be felled into the setting will require approval from AVCF prior to falling. AVCF is to be notified immediately.

2) Leave trees may be substituted if, for safety reasons, a faller feels it is necessary to do so, but alternate leave trees must be retained and should be well rooted and of the same species and diameter

YARDING and LOADING PRESCRIPTIONS

- 1) No roadside landing of logs within 3 meters of any streambank along all roadsides. All drainage structures will be maintained and remain functional.
- 2) Avoid excessive ground lead gouging due to high to very high surface erosion potential. If soil disturbance occurs, then grass seeding will be required.
- 3) During the bark peeling stage of growth, the tree bole is highly susceptible to damage. Contact with retention trees during harvesting operation should be avoided between April 1 st and June 15 th.
- 4) No more than 10% of the retention trees in the aggregate or dispersed retention areas or single retention trees in this cutblock may have significant damage.

Significant damage to Hw, Fd, and Cw is defined as a tree with:

One or more wounds (i.e. exposed cambium) that girdle more than 1/3 the circumference of the stem.

 $Any \ wounds \ on \ a \ supporting \ root \ within \ one \ metre \ of \ the \ stem. \ A \ gouge-a \ wound \ that \ penetrates \ (splintered) \ into \ the \ sapwood \ or \ deeper.$

Additionally, for Hw and Cw only: A wound >400cm² on the stem.

SAFETY

In-block safety hazards associated with block TS2 have been identified on the harvest instruction maps. In the event additional in-block safety hazards (temporary or permanent) are encountered or develop during road construction or harvesting phases, a plan must be developed to address the hazard. Any identified permanent hazards must be reported back to AVCF (using Hazard/Issue Report Form).

Road segments with gradients > 18% have been identified on the Harvest and Road instruction Plan Map en route to the setting. Prior to commencing log hauling operations the contractor must perform a risk assessment of the current conditions and adjust hauling activities to suit the traction conditions. Hauling for K1 will not be permitted when ice and or snow is on the logging roads leading to or in the given setting (very low traction level). This has been determined using FERRIC step grade decent guidelines. The Ministry of Transportation guidelines are to be followed when hauling on the highway.


SPECIFIC BLOCK SAFETY COMMENTS


- * Colluvium within the cutblock could roll during harvesting activities.
- * Grades >18% are proposed within cutblock tsa and along the access route. Supervosors should complete a steep grade assessment prior to comensing hauling operations.
- * Public hiking trails exist adjacent to this block. Proper signage and public awareness must be addressed during all phases of HARVESTING.

HARVESTING ISSUES

- This setting will be helicopter and cable yarded.
- * Hand falling will be required for cutblock ts2.
- * Utlize branch ta568, ta568j and ta568d for heli drop zones. Do not impact adjacent plantations.
- * All persons working in this setting should be aware of steep ground, small rock outcrops, large boulders/ rock fall hazards, slope instability and sensitive areas within and adjacent to the falling boundary. All these areas are identified on the harvesting map. Note the rock fall hazards worker safety alert locations.
- * Uniformly dispersed leave trees have been retained within the harvest areas as part of the "legal requirements" for cutblock's located within the sproat lake special management zone no. 17. As such, these trees have been selected and marked /identified with a blue panted "I" for leave tree. They are not to be cut or damaged during cutblock development.

E.1 RIPARIAN MANAGEMENT STRATEGIES Creek I.D. CLASS MANAGEMENT STRATEGIES FOR RIPARIAN MANAGEMENT ZONES (RMZ) INCLUDING PROTECTING STREAM NCD NCD(s) within the harvest area will be FX and YX. No RMZ is required. Note all streams lie within the Sproat Lake Community Watershed, minimize sedimentation at all costs. STREAM REACH AND RMA IS OUTSIDE OF THE HARVEST AREA S3 STREAM REACH OUTSIDE HARVEST AREA, PORTIONS OF THE RMA WITHIN THE HARVEST AREA PORTIONS OF STREAM REACH AND RMA ARE WITHIN THE HARVEST AREA 4 (R2), 4B, 4C AC Cleaning to be assessed post-yarding prior to block completion. FA/BL Fall Away. Timber is to be felled away. Leaners and hazard trees that cannot be safely felled away shall be felled and left bridging the stream Fall Away. Timber is to be felled away. Yard Away. Timber is to be yarded away. In order to improve deflection, cables are allowed to be suspended above the stream. Non-fish streams: merchantable leaners and danger trees that have been felled across the stream will, by necessity, be yarded across the streams: Leaners and danger trees which have been felled across the stream will be left unless detrimental to the stream. HH 100% harvested (no retention of saplings) RS Retain saplings on the streambanks (non-merchantible) Feathered edge. FE BPT Blue painted trees (selected for removal). Faller's choice of alternate tree if unable to fall painted tree safely NHZ No harvest zone. Trees are to be felled away from the zone. Safe trees that cannot be felled away are to be left as part of the NHZ. Danger trees must be felled and will be left for future LWD or be removed if detrimental to the stream FX Fall Across YX Yard Across. Maximize deflection to minimize stream bank disturbance YV Yard vertically Machine free zone MFZ Machine Clean transportable introduced large woody debris (LWD) and accumulations concurrent with varding MC HC Hand Clean introduced transportable debris





ROAD INSTRUCTIONS – OPENING#TS2

ACCESS ROAD: TA568 CUTTING PERMIT: N0.9 TIMBERMARK: K2D/0R1

RAINFALL SHUTDOWN CRITERIA

Shutdown Criteria: Activities must shut down if: The total rainfall reaches 58 mm in 24 hours. Onsite rain gages should be used and monitored daily.

Start-Up Criteria: Activities may start-up when: The total rainfall is equal to or less than 30 mm in 24 hours. Refer to the Return to work guide in the tender document for more information.

Adequate recovery time should be given before building operations commence after a shutdown.

ROAD NAME	START STATION	END STATION	TYPE OF WORK/COMMENTS
TA568	2+209	3+099	Road Reactivation
TA568J	3+099=0+000	0+888	New Construction
TA568G	0+000	0+063	New Construction
TA568H	0+000	0+099	New Construction

ROAD NAME	STATION	RIPARIAN ID	RIPARIAN CLASS	DEBRIS TRANSPORT POTENTIAL	CULVERT/ BRIDGE SIZE	DESIGNED PEAK FLOW	Special instructions for operations within or adjacent to RMA
TA568	2+213	-	-	-	600	X-Drain	
TA568	2+390	=	-	-	600	X-Drain	
TA568	2+650	-	-	-	600	X-Drain	
TA568	2+787	-			600	X-Drain	
TA568	2+827	-	S3	Low - Moderate	1200	Q-100	
TA568	2+890	-	S4	Low	800	Q-100	
TA568	2+931	5	S3	Moderate-High	1x5	Q-100	
TA568	2+984	-	-	-	600	X-Drain	OPENING TS2 LIES WITHIN THE SPROAT LAKE COMMUNITY
TA568J	0+091	4B	S4	Low	600	Q-100	WATERSHED. ALL STREAM CROSSINGS ARE TO BE ARMORED WITH COARSE ROCK MATERIAL TO MINIMIZE THE TRANSPORT OF FINES
TA568J	0+289	4B	S4	Low	600	Q-100	DOWN STREAM.
TA568J	0+561	-	-	-	600	X-Drain	DOWN OTHER WILL
TA568J	0+637	4C	S4	Low	600	Q-100	
TA568J	0+703	-	-	-	600	X-Drain	
TA568J	0+794	-	-	-	600	X-Drain	
TA568G	0+009	-	-	-	600	X-Drain	
TA568H	0+064	-	-	-	600	X-Drain	

GENERAL INSTRUCTIONS

All employees, supervisors and contractors associated with these Harvest Instructions shall be fully advised of their contents and requirements.

All litter including cable, oil buckets, grease tubes, newspapers, and lunch garbage is to be placed in appropriate garbage containers and removed from the site for proper disposal concurrent with all operations.

ADDITIONAL INSTRUCTIONS

- [1] R/W clearing widths to be 20 meters unless a larger width is required for safety or otherwise prescribed.
- [2] Prior approval must be obtained from AVCF if falling beyond right-of-way clearing is required for spoil sites or quarries.
- [3] Proposed cross-drain culvert locations are approximate. Site specific installation to within ±25m is acceptable. Installation beyond this distance constitutes a 'change of plan' and requires prior approval from AVCF.
- [4] Equipment must not be fuelled or serviced within the riparian management area (RMA) of a stream, lake or wetland. Do not park any equipment within an RMA overnight.
- [5] Affected water licensees or affected water purveyors must be notified at least 48 hours before commencement of road construction, re-activation or deactivation in a community watershed.
- RMA distances: STREAMS: S1 70 meters, S2 50 meters, S3 40 meters, S4 30 meters, S5 30 meters, S6 20 meters, LAKES: L1 10 meters, L3 30 meters, WETLANDS: W1, W5 50 meters, W3 30 meters.
- [6] Avoid quarry locations within the RMA of any stream; where avoidance is not practical, quarries may be located within the RMA of a S6 stream if no impacts (i.e. increased sedimentation) will occur to the stream. All other streams (i.e. S1 to S5) require prior approval from AVCF before a quarry may be located within its RMA. Do not deck or process wood within RMA's.
- [7] Cultural Resources: If an unidentified cultural heritage resource is encountered within the cutblock during any harvesting phase, operations will cease in the immediate vicinity of the feature and AVCF shall be notified [8] Wildlife Resources: In the event any unidentified bear dens or raptor nest trees are encountered during falling, but before the tree has been cut, the faller will go elsewhere for the day and report this potential wildlife tree
- to a AVCF Supervisor. Fallers are not to return to the vicinity of the wildlife tree until notification from AVCF has been given. If the discovery of a bear den or potential nest tree occurs while the tree is being felled, the decision to proceed is at the faller's discretion in regards to safety and Worksafe BC requirements. If it is unsafe to leave the tree partially cut, the faller will complete falling the tree and report the incident to AVCF.
- [9] Fish Streams: Due to the close proximity of fish streams immediately downstream of the cutblock, ensure a high level of diligence is maintained regarding stream bank protection, in-stream woody debris disturbance and protection of stream banks at designated crossings.

[10] Invasive Plants: Broom occurs along sections of TA568. Follow FSP measures for invasive plants. Cut and remove plants in association with road reactivation, clean machinery as required. Monitor and treat broom and other

invasive species during early establishment. Grass seed exposed soil on or adjacent to roads, trails, and landing sites as soon as possible following harvest. **FALLING of SNAGS and DANGER TREES**

In accordance with the Cutting Permit Authority and WorkSafe BC Regulations, all snags and danger trees that endanger workers within a distance of 50m outside the cutblock boundaries, or within one and a half tree lengths, (whichever is greater), are approved for falling under these harvest instructions. All danger trees and snags outside the cutblock boundaries that are required to be felled must be recorded on a map and provided to AVCF once falling has been completed. AVCF will be notified immediately if danger trees and/or snags are identified in groups and removal will result in the cutblock boundary being substantially impacted. Felled snags and danger trees up to 50m outside of the falling boundary meeting utilization specifications will be recovered.

EXCEPTION- Wildlife Tree Patch (WTP) areas and OLD Growth Management Areas (OGMAs) - Snags or danger trees can be felled within a WTP or OGMA for safety reasons although only the portion of the felled snag or danger tree that falls outside the WTP can be recovered.


CUTBLOCK BOUNDARY TREATMENTS


All marked boundary trees except snags and danger trees must remain standing during and after the completion of harvesting. Trees located along and adjacent to the cutblock edges (i.e. within the harvest boundary) that must be felled outside the harvest area must be recovered unless a physical, safety or environmental issue exists (e.g. deep gullies, steep breaks, fish creek, etc.). Trees that cannot be recovered may be left standing, if they are safe to leave, as wildlife trees. These trees must be recovered on a map and provided to AVCF once falling is complete; If unsure how to proceed, contact AVCF.


SAFETY


Road and in-block safety hazards associated with block TS2 have been identified on the harvest and road instruction maps. In the event additional in-block safety hazards (temporary or permanent) are encountered or develop during road construction or harvesting phases, a plan must be developed to address the hazard. Any identified permanent hazards must be reported back to AVCF (using Hazard/Issue Report Form).


Road segments with gradients > 18% have been identified on the Harvest and Road instruction Plan Map en route to the setting. Prior to commencing log hauling operations the contractor must perform a risk assessment of the current conditions and adjust hauling activities to suit the traction conditions. Hauling for TS2 will not be permitted when ice and or snow is on the logging roads leading to or in the given setting (very low traction level). This has been determined using FERRIC step grade decent guidelines. The Ministry of Transportation guidelines are to be followed once on the highway.

































P-Stn m.	Field Ref.	SsI %	Ssr %	Bank Ht. L m.	Bank Ht. R m.	SG Cut V. Cu. m.	SG Fill V. Cu. m.	Strip V. Cu. m.	Mass H. Cu. m.	Lyr1 Gnd	Lyr2 Gnd	Lyr3 Gnd	BERNI VAL
0.0 19.6	0.0 19.6	0 -16	0 57	-0.2	2.9	61.0 136.3	31.0 12.6	16.8 12.7	0.0 29.9	OB OB	GT GT	R1 R1	28 000 E
32.3 46.0	32.3 46.0	-16 -45	68 65	-0.2 -0.2	5.3 5.0	218.3	0.3	13.5	153.6 371.6	OB OB	GT GT	R1 R1	F 00000 0
59.7	59.7	-56	80	-0.2	6.4	240.6 345.2	0.2 0.0	13.5 17.3	612.0	ОВ	GT	R1	
77.3 85.3	77.3 85.3	-80 -8	58 83	-0.2 -0.2	5.5 8.7	196.6	0.3	8.1	957.2 1153.5	OB OB	GT GT	R1 R1	Wall to the Control of the Control o
91.3	91.3	-41	105	-0.2	6.9	152.7 343.9	13.3 19.0	7.9 17.9	1292.9	OB	GT	R1	YTIM
106.8 119.7	106.8 119.7	-65	65 64	-0.2 -0.2	5.8 5.1	235.1	0.0	12.4	1617.8 1852.9	OB OB	GT GT	R1 R1	
141.1	141.1	-50 -59	53	-0.2 -0.2	4.0	312.9	3.9	21.4	2161.9	OB OB	GT	R1	
158.8	158.8	-35	33	-0.2	2.7	200.8 36.2	13.2 99.1	19.2 12.4	2349.5	OB	GT	R1	Cutblock: TS2
169.7 175.2	169.7 175.2	-35 -23	35 7			0.0	108.3	7.2	2286.7 2178.4	OB OB	GT GT	R1 R1	Road: TA568J
186.9	186.9	3	-3			0.0 36.1	143.4 62.5	12.5 10.6	2035.0	ОВ	GT	R1	
197.2 208.4	197.2 208.4	75 76	-37 -15	3.8 5.5	-0.2 -0.2	128.2	12.2	11.7	2008.6 2124.6	OB OB	GT GT	R1 R1	
217.4	217.4	38	-44	0.9	-0.2	75.3 72.5	38.1 21.6	10.1 10.0	2161.8	ОВ	GT	R1	Road Design
226.4	226.4	25	-31	2.9	-0.2	119.2	8.8	14.8	2212.7	OB	GT	R1	0+000 to 0+888
242.3 257.1	242.3 257.1	24 33	-35 -37	1.0 1.6	-0.2 -0.2	54.7	24.3	14.4	2323.0 2353.5	OB OB	GT GT	R1 R1	
263.1	263.1	37	-43	1.2		21.2 76.1	21.2 27.2	6.6 11.8	2353.5	ОВ	GT	R1	
274.5 287.4	274.5 287.4	44 51	-46 -54	3.0 2.6	-0.2 -0.2	121.8	0.8	11.4	2402.4 2523.3	OB OB	GT GT	R1 R1	APPRAISAL DATA
289.4	289.4	48	-50		-0.2	8.5 28.5	23.4 111.4	2.6 11.7	2508.4	OB	GT	R1	TABLE
298.4 304.1	298.4 304.1	73 60	-18 -53	3.4 5.1	-0.2	73.1	1.7	5.5	2425.5 2496.9	OB OB	GT GT	R1 R1	Notes:
317.0	317.0	72	-53 -48	6.1	-0.2 -0.2	262.2 252.6	0.1 0.0	12.9 10.5	2759.1	OB OB	GT	R1	(1) Side Slopes are derived from
327.4	327.4	67	-66	6.7	-0.2	207.6	0.0	9.0	3011.6	ОВ	GT	R1	an average of the first slope %
336.2 359.1	336.2 359.1	45 84	-63 -33	5.5 3.4	-0.2	300.8	47.3	25.3	3219.2 3472.6	OB OB	GT GT	R1 R1	measured off of centerline in 20 meter segments.
372.1	372.1	91	-45	5.5	-0.2	108.8 49.9	87.5 57.0	16.9 8.8	3493.9	ОВ	GT	R1	(2) Watch for rockfall in steep areas.
378.1 396.9	378.1 396.9	82 64	-48 -68	3.1 6.5	-0.2	274.2	81.3	23.2	3486.8 3679.8	OB OB	GT GT	R1 R1	(3) Follow BCTS Rainfall
411.9	411.9	54	-68	4.3	-0.2	313.7 91.1	0.0	14.2 8.4	3993.4	ОВ	GT	R1	Guidelines. (4) Background information is
420.9	420.9	39	-41	2.0	-0.2	55.4	1.6 1.7	8.4	4082.9	OB	GT	R1	approximate. Refer to construction and harvest maps.
430.7 441.7	430.7 441.7	31 27	-19 -13	1.7	-0.2	24.0	57.5	10.1	4136.5 4103.0	OB OB	GT GT	R1 R1	and harvest maps.
449.5	449.5	17	-10			0.0 42.2	108.0 80.7	8.3 15.0	3995.1	ОВ	GT	R1	
465.0 480.7	465.0 480.7	-18 -29	9 42	-0.2 -0.2	1.4 2.5	134.0	7.5	16.6	3956.6 4083.1	OB OB	GT GT	R1 R1	
492.6	492.6	-26	42	-0.2	1.8	68.9 121.8	13.6 4.9	11.4 15.3	4138.4	OB	GT	R1	
508.9 533.5	508.9 533.5	-30 -29	4 14	-0.2 -0.2	1.1 1.0	118.8	46.6	25.8	4255.3 4327.5	OB OB	GT GT	R1 R1	
560.5	560.5	-37	17	0.2	0.4	67.6 65.1	107.4 77.4	30.1 27.5	4287.7	ОВ	GT	R1	
587.3 603.3	587.3 603.3	-26 -35	36 54		1.4	57.1	77.4	18.1	4275.4 4255.0	OB OB	GT GT	R1 R1	
618.3	618.3	-34	82	-0.2	1.9 4.4	97.8	102.4	18.5	4250.4	OB OB	GT	R1	
637.3	637.3	-24	70	0.0	2.3	100.1 50.5	122.1 34.8	21.5 10.7	4228.3	ОВ	GT	R1	
648.0 678.3	648.0 678.3	-31 -41	55 37	-0.2	2.9 0.4	144.0	57.8	30.2	4244.0 4330.2	OB OB	GT GT	R1 R1	
702.9	702.9	-45	58		2.4	71.7 31.2	102.9 43.0	27.6 10.1	4298.9	ОВ	GT	R1	
711.7 720.7	711.7 720.7	-36 -38	50 68		1.3 0.8	13.3	114.3	11.6	4287.1 4186.1	OB OB	GT GT	R1 R1	
728.6	728.6	-46	49	-0.2	1.8	22.4 216.8	78.6 0.0	9.1 15.2	4130.0	OB	GT	R1	
742.6 749.6	742.6 749.6	-37 -28	32 -16	1.4 2.8	4.0 3.7	210.2	0.0	7.3	4346.8 4557.0	OB OB	GT GT	R1 R1	
763.5	763.5	30	-29	4.8	2.2	458.9 279.1	0.0 0.0	15.1 16.5	5015.9	ОВ	GT	R1	
780.5	780.5	34	-60	2.5	-0.2	75.9	12.9	16.5	5295.0	ОВ	GT	R1	
793.5 804.4	793.5 804.4	34 45	-30 -40	1.3 0.8		22.9	73.0	12.8	5357.9 5307.8	OB OB	GT GT	R1 R1	Designed by
816.1	816.1	12	-20	0.3	-0.2	14.7 25.6	86.6 29.9	14.0 10.6	5235.9	ОВ	GT	R1	Meridian Forest Services #15 1010 Shearme Road
825.8 836.5	825.8 836.5	38 12	-39 -12	1.7 0.5	-0.2 -0.2	34.7	23.2	10.9	5231.6 5243.2	OB OB	GT GT	R1 R1	Coombs BC, V0R1M0 www.meridianforest.ca
851.8	851.8	3	5	1.0	1.0	84.9 74.9	0.4 0.0	13.2 15.4	5327.7	OB	GT	R1	
866.6 888.0	866.6 888.0	-8 0	-3 3	-0.2 -0.1	0.1	57.5	0.0	19.7	5402.6 5460.1	OB OB	GT GT	R1 R1	MERIDIAN MERIDIAN
000.0	000.0	U	3	-0.1	0.1				5460.1	OB	GI	KI	Forest Services Ltd.
			.							\\MSERVER\Clients\	Alberni Valley Commu	unity Forest Corp\	
Alberni Va	alley Comi	munity Fore	est		ROAD:	TA568J	Cutblock	k: T S2		Cutblocks\2015\TS2 TA568-data.dsn	Taylor Mt. Adder\Roa	nds\Design\TA568\	16/02/17 Page 1 of 1
	-	-								i AJUO-uata.USII			









P-Stn m.	Field Ref.	Ssl %	Ssr %	Bank Ht. L m.	Bank Ht. R m.	SG Cut V. Cu. m.	SG Fill V. Cu. m.	Strip V. Cu. m.	Mass H. Cu. m.	Lyr1 Gnd	Lyr2 Gnd	Lyr3 Gnd	BERNI VAL
0.0 7.0 9.3 13.4 20.7 34.3 40.3 63.2	0.0 7.0 9.3 13.4 20.7 34.3 40.3 63.2	0 5 15 10 5 10 25 -60	0 -8 -25 -15 -10 -25 -10	0.0 0.3 1.5 1.6	-0.2 -0.2 -0.2	0.0 0.0 0.5 9.7 68.1 52.9 65.3	22.0 24.8 35.7 5.6 0.0 0.0 110.5	16.1 7.1 12.1 17.6 26.3 17.4 85.0	0.0 -22.0 -46.7 -81.9 -77.7 -9.6 43.2 -2.0	BR GT OB OB OB OB OB	GT GT GT GT GT GT	R1 R1 R1 R1 R1	TST STINGHEN CONTRACTOR
													Cutblock: TS2 Road: TA568G
													Road Design 0+000 to 0+063
													APPRAISAL DATA TABLE
													Notes: (1) Side Slopes are derived from an average of the first slope % measured off of centerline in 20 meter segments. (2) Watch for rockfall in steep areas. (3) Follow BCTS Rainfall Guidelines. (4) Background information is approximate. Refer to construction and harvest maps.
													Designed by Meridian Forest Services #15 1010 Shearme Road Coombs BC, V0R1M0 www.meridianforest.ca
										Z:\Alberni Vallev Co	ommunity Forest Corp\Cu	tblocks\2015\TS2	MERIDIAN Forest Services Ltd.
Alberni Va	alley Comm	unity For	est		ROAD:	TA568G	Cutbloc	k: TS2		Taylor Mt. Adder\Ro	pads\Design\TA568G Des	sign\TA568G-data.	15/12/11 Page 1 of 1







P-Stn	Field Ref.	Ssl %	Ssr %	Bank Ht. L	Bank Ht. R	SG Cut V.	SG Fill V.	Strip V.	Mass H.	Lyr1 Gnd	Lyr2 Gnd	Lyr3 Gnd	RNI VA.
m. 0.0 6.2 20.9 35.8 47.8 63.6 83.5 98.5	0.0 6.2 20.9 35.8 47.8 63.6 83.5 98.5	-31 -41 -52 -31 -42 -21 -10		m. 43 -0.7 20 -0.2 48 -0.2 36 52 33 0 -0.2 20	m. 2.9 2.1 2.6 0.8 2.4 0.5 0.6 0.3	Cu. m. 37.6 69.4 49.3 36.4 39.4 65.4 52.8	Cu. m. 3.1 27.6 53.5 54.7 102.3 78.3 31.4	Cu. m. 5.8 15.2 15.7 13.8 20.1 22.2 14.7	Cu. m. 0.0 34.5 76.3 72.0 53.7 -9.2 -22.1 -0.7	OB OB OB OB OB OB OB	GT GT GT GT GT GT GT	R1 R1 R1 R1 R1 R1 R1	TSTON ATINGMENT OF THE PROPERTY OF THE PROPERT
													Cutblock: TS2 Road: TA568H
													Road Design 0+000 to 0+099
													APPRAISAL DATA TABLE
													Notes: (1) Side Slopes are derived from an average of the first slope % measured off of centerline in 20 meter segments. (2) Watch for rockfall in steep areas. (3) Follow BCTS Rainfall Guidelines. (4) Background information is approximate. Refer to construction and harvest maps.
													Designed by Meridian Forest Services #15 1010 Shearme Road Coombs BC, V0R1M0 www.meridianforest.ca
													MERIDIAN Forest Services Ltd.
Alberni Va	alley Com	munity Fo	rest	,	ROAD:	TA568H	Cutbloc	k: TS2	,	\\MSERVER\Clients\ Cutblocks\2015\TS2 Design\TA568H-data	\Alberni Valley Commu ? Taylor Mt. Adder\Roa a.dsn	unity Forest Corp\ ds\Design\TA568H	15/12/11 Page 1 of 1



Alberni Valley Community Forest

TA568 ROAD RECONSTRUCTION PRESCRIPTION

Prepared by:	Darin Brown, Meridian Forest Services Ltd.
Assessment date:	September 3 rd , 2015 – Carsten Durkop, Meridian Forest Services Ltd.
Standard:	TA568 will be reactivated to hauling status. Recommended actions are to be completed to the required road building standards as defined in the <i>Forest Engineering Guidebook</i> , 2002.
Road Section:	The Point of Commencement (P.O.C) for the TA568 Reconstruction Plan is at Station 2+209, at the junction of TA568D Station 0+000
Safety:	Supervisors are required to read and understand findings, recommendations and safety concerns of any report, including this report. Prior to start-up this information must be reviewed, discussed and recorded with the construction crew during the Pre-work inspection. Some general safety notes are: There is no industrial activity and log or equipment hauling in this area. Radio communication is on the Sproat Lake repeater. The onsite construction crew may also communicate on their own frequency. The radio frequencies and contact information must be reviewed with all of the construction crews and recorded in the Pre-work inspection report prior to the reconstruction start-up. Any additional construction crews working on the site must also be informed of the correct radio frequencies and procedures. Due to the location of the road within the Sproat Lake community watershed, Coastal Rainfall Shutdown Guidelines must be strictly adhered to. The reactivation crew must ensure they minimize the amount of sediment entering watercourses. They should also be aware that periods of intense precipitation may cause instability in freshly excavated cutbanks / fill slopes, even prior to reaching shutdown guidelines. Best practices are to shut down if drainage systems are overflowing or if surface sediments are saturated.
General Notes:	All the culverts mentioned in this report are field referenced with pink culvert ribbons. See accompanying map for station locations and points. Construction prescriptions were marked in the field White and Green Ribbon with stations, see accompanying map for prescriptions and this report. The ditching/brushing prescriptions can be modified or added to at the discretion of the machine operator. Some of the material in the ditches are ideal for road surfacing and may be utilized on the road. All operations are located within the Sproat Lake Community Watershed. All streams are none fish, but have appropriate riparian reserves setbacks as if as fish streams.





Alberni Valley Community Forest

TA568 RECONSTRUCTION – DETAILED PRESCRIPTION

Start Station	End Station	Dist. (m)	Station In Field	Action	Comments		
2+209			1		The Point of Commencement (P.O.C) for the TA568 Reconstruction Plan is at Station 2+196, at the junction of TA568D Station 0+000		
2+209	3+099	890	1-14	BRUSHING	Brushing is prescribed for the entire reconstruction leng but the amount of brushing required will fluctuate over this stretch of road.		
2+226			2	Install 600mm CMP	Cross Drain. No Stream. Old rotten 0.5 x 2.0m WBC.		
2+403			3	Install 600mm CMP	Cross Drain. Replace old 1 x 3.0m hemlock WBC.		
2+663			4	Install 600mm CMP	Cross Drain. No Stream. Old rotten 0.5 x 2.0m WBC.		
2+794			5	Remove 10m of reactivation material	There is capping material which was removed from the deactivation of the WBC on Stream #5 and spoiled on the fill slope. Remove the material to the designated spoil site at Spur 1.		
2+794	2+804	10	5	WIDENING	Narrow running surface due to deactivation material spoil don fill slope of the road.		
2+800			6	Install 600mm CMP	Cross Drain. No Stream. Plugged 600mm CMP.		



A SESUL MANERAL

Alberni Valley Community Forest

	 112011	in valley comin	Total Total
2+811	7	Remove old WBC structures	There are old sills and stringers on the road due to the deactivation of the WBC on Stream #5. Remove the material to the designated spoil site at Spur 1.
2+830	8	Start of reconstruction	Large fill required.
2+840	9	Install 1200mm CMP	S3 Stream.
2+843	10	End of reconstruction	Large fill required.
2+903	11	Install 800mm CMP	S4 Stream.
2+944	12	Install 1x5m WBC	Stream #5 (S3)
2+997	13	Install 600mm CMP	Cross Drain. No Stream.
3+099	14	mount occinin Civil	The Point of Termination (P.O.T) of the TA568 Reconstruction Plan. Point of Commencement (P.O.C.) of new construction Station 0+000 of TA568J





Alberni Valley Community Forest

<u> </u>	<i>J</i>	
Culvert Size	Length (m)	Number of Units
600mm CMP	10	5
000IIIII CMF	12	
200mm CMD	10	1
800mm CMP	12	
1000mm CMD	10	
1000min CMP	12	
1200mm CMD	10	1
1200min CMP	12	
1m x 5m WBC	~	1
TA568	875m	Brushing as required, Amounts
		will fluctuate.
TA568	~	Minor ditch cleaning
		throughout.
TA568	10m	
TA568	13m	
TA568	~	Grading may be required after
		road rehab is complete.
	Culvert Size 600mm CMP 800mm CMP 1000mm CMP 1200mm CMP 1x 5m WBC TA568 TA568 TA568 TA568	Culvert Size Length (m) 600mm CMP 10 800mm CMP 10 100 12 100 12 100 12 12 10 12 12 12 12 12 12 12 875m TA568 875m TA568 10m TA568 13m



Appendix 3.5: Log Culvert Design

Terminology

For the purposes of this manual, the term "log culvert" is interchangeable with "woodbox culvert," "log stringer culvert," or "wood stringer culvert."

Definition: Log Culvert

A log culvert is a log crossing structure having a span of less than 6 m centre-to-centre of bearing, and an abutment height (if constructed as a log crib) of less than 4 m between the underside of the lowest crib log to the underside of the stringers, and is used to carry ephemeral or perennial stream flow in a stream channel from one side of a road to the other. A log culvert structure is covered with soil and lies below the road surface (Figure 3-14).




Figure 3-14 Simple log culvert

Notes Figure 3-14:

- Opening size: passes peak flow for 10-year or 100-year return period, (depending on the anticipated time that the log culvert will remain on the site) plus minor debris.
- Road width: varies with road curvature.
- Log culvert length (as measured parallel to stream): varies with road width, height and type of fill, culvert gradient and skew.
- Sill logs: place outside the stream channel width and below scour level: species can vary. Use minimum diameter of about 300 mm; long enough to support stringers, fill containment logs, and road fill.
- Non-woven geotextile (filter cloth).
- Stringers (puncheon): match in diameter and taper, and be free of decay and excessive crook or sweep; spiral grain should be less than 1 in 8. Knot size in middle is less than 125 mm. See <u>Table 3-8</u> for sizing.

- Fill containment logs: minimum diameter 400 mm. See <u>Figure 3-15</u>. If lashing is used, inset the cable to protect it from damage by road maintenance equipment.
- Connections:
- Stringers to sill; 12 mm spiral drifts
- Fill containment log to sill: 19 mm spiral drifts or four wraps of 19 mm diameter 6 x
 9 fibre core wire rope
- Inlet control: place shot rock to protect against fill erosion below the design flood level.
- Outlet control: place rock as required to prevent outlet scouring and undermining of the sill logs.
- In the case of a skewed log culvert, measure the span of the stringers for design purposes from bearing to bearing along the stringers and not at right angles to the sill logs.

Consider log culverts for:

- streams where other resource agencies require the culvert to be open bottomed; and
- steep gradient streams.

Where the planned service life of the road is less than the life expectancy of the drainage structure components, consider using log culverts:

- as temporary structures on tote roads or pilot trails;
- on roads where ongoing minor debris problems are anticipated; and
- on permanent roads as temporary drainage structures at the clearing or subgrade construction stage, until the permanent drainage structures are installed.

Ensure that a log culvert design addresses the following:

- opening size for design flow and debris management;
- culvert length and fill and surfacing requirements;
- superstructure design (stringer or puncheon sizing);
- substructure design (sills, mud sills, and foundation logs); and
- inlet and outlet protection requirements.

Log culvert opening size

To meet current legislative requirements, design a log culvert to pass the highest peak flow of the stream that can reasonably be expected within the following return periods specified below for the length of time it is anticipated that the log culvert will remain on site (see FPPR section 74). For methods to estimate the value of Q_{10} and Q_{100} , design discharge of a creek see Figure 3-3: High water estimation method for stream culverts in this chapter and <u>Chapter 4.8: Design Discharge Criteria</u>.

Anticipated period that the log culvert will remain on the site	Peak flow return period
For a log culvert that will remain on site for up to 3 years	10 years (i.e., Q ₁₀)
For a log culvert that will remain on site for over 3 years	100 years (i.e., Q ₁₀₀)
For a log culvert within a community watershed that will remain on site for over 3 years	100 years (i.e., Q ₁₀₀)

Table 3-8 Peak flows for various log culvert lifespans

A log culvert is a type of open bottom structure, designed to span the stream channel width. This is particularly important on fish-bearing streams to avoid impacts on fish habitat and fish passage (refer to the section on "Open bottom culverts" in the <u>Fish-stream Crossing Guidebook</u> page 6).

In addition to passing the required peak flow discharge, design log culverts to manage anticipated debris. Options may include, but are not limited to:

- increasing the opening size (height and/or width);
- allowing debris to pass over the approaches;
- trapping debris with a specially fitted trash rack or other device; and
- combining these and other options.

Inspect debris catchment devices frequently and clean them as required. The criteria for design of any debris catchment device are site-specific and may incorporate professional input. Identify debris problems from terrain hazard maps, air photo interpretations, field investigations, and reports for the area (see the <u>Gully Assessment Procedure Guidebook</u>).

The convention for specifying the opening size (inside measurements) of a log culvert is height (vertical distance between the deepest point along the channel floor and the soffit of the stringers) followed by the width (horizontal distance measured at right angles between the inside face of the sill logs).

Log Culvert Length

Culvert length, as measured in the direction of the stream, is determined by the following:

- road width;
- depth of road fill over the log culvert, and fill slope angles;
- type of fill over the log culvert;

- inlet and outlet treatments;
- culvert gradient; and
- culvert skew.

Road Width

If the culvert is located within a horizontal curve, provide for extra road width to accommodate side tracking of logging trucks and hence additional culvert length. The required width can be found in <u>Table 3-3</u>: Curve widenings.

Depth of Road Fill

Road fills greater than 2 metres on top of the log stringers should generally be avoided. Should a failure occur, there is a potential for large volumes of sediment-producing materials to enter the stream channel. In addition, deep fills make culvert replacement, repairs or even inlet clean-out difficult. For fills anticipated to exceed depths of 2 metres, ensure that a professional engineer has been consulted or a design table produced by a professional engineer which captures the fill depth is used.

Measures to reduce road fill depth include:

- use of a longer span culvert, or a bridge for V-shaped channels;
- increasing the culvert height, by use of log cribs; and
- relocation of the road to a more suitable crossing.

Ensure that log culverts are sufficiently long to contain the fill and prevent material from entering the stream. As the fill height increases for a given roadway width, increase the culvert length.

Incorporate road fill containment measures into the design. This can be achieved by making the culvert extra long (at least 1 m per side beyond the toe of the road fill) and securing a large containment log (at least 400 mm diameter) at the toe (Figure 3-15.).




Figure 3-15 Fill containment for log culvert

In addition, include provisions that prevent road fill materials from encroaching on the design peak flow discharge flood level. For fills up to 1 m thickness, use the sill logs—provided they are long enough—for this purpose. For higher fills, incorporate other site-specific measures into the design.

Type of Road Fill

To maximize fill slope angles and minimize culvert length, use shot rock or granular pit-run material for the fill material placed over a log culvert. Avoid the use of silty and clayey materials because these materials require flatter fill slope angles (and therefore longer slope lengths) to maintain fill slope stability, and increase the potential for sedimentation.

Log Culvert Gradient

For stream gradients less than 10%, place the stringer soffit (culvert soffit) at 0% grade or at or near the same gradient as the stream. Should the proposed culvert soffit gradient (not the stream channel gradient), exceed 10%, then apply other structural considerations.

Channel Gradients Less than 10%

A cross-sectional sketch of the culvert, the fill, and a profile of the stream bed provide the best tools for determining log culvert length. Measure the required length directly from a sketch drawn to scale.

Channel Gradients Greater than 10%

Measure the length directly from the cross-sectional sketch for the stream.

Inlet and outlet treatments

Incorporate headwalls or sill logs into log culvert design, allowing vertical end fills and therefore reduced culvert length.

Length for skewed culverts

Where a culvert crosses the roadway at other than a right angle to the road centreline, allow for the increased culvert length caused by this skew.

Log culvert stringer selection

Stringer sizing involves selection of the appropriate log diameter and species to be used for the stringers. <u>Table 3-9</u> is an example of a log stringer sizing table developed by a professional engineer. <u>Table 3-9</u> presents stringer sizing for log culverts, as a function of span (see <u>Figure 3-15</u>), total fill depth, logging truck axle loads (e.g., L75), and log species. In this professionally engineered table, the total fill depth is the combined thickness of road surfacing and underlying road fill materials that extend down to the top of the stringers. The log diameters given in Table 3-9 are minimum mid-diameters, which are measured at mid-span under the bark. The total fill depth ranges from a minimum of 300 mm to a maximum of 2 m for this table.

If the design discharge is 6 m³/sec or greater, or the road fill depth is greater than 2 m, ensure that a professional engineer has been consulted or a design table produced by a professional engineer which captures the fill depth is used.

Use oversize logs to account for unseen flaws, to give added strength for overloads and general heavy use, and to extend the service life of the structure. For maximum service life, use sound western red cedar. Fill containment logs contain the fill or road surfacing and can be structural or non-structural. Firstly, place a geosynthetic over the stringers to prevent surfacing or fill material from migrating between the stringers and into the watercourse.

Log culvert substructure design

The substructure required depends on the bearing capacity of the foundation soils and the length and diameter of the logs available. Choice of substructure is based on an estimate of the bearing strength of the soil at the site. From this, determine the diameter and length of the logs needed to support the design loads. Refer to FPInnovations' Log Bridge Construction Handbook (1980) for a detailed explanation of this topic.

Single sill logs

Use single sill logs as culvert foundations if the ground is firm and the sill log provides sufficient clearance for the design flood and debris passage. Use a minimum diameter for sill logs of about 300 mm. For short service-life culverts (planned for less than three years use), almost any species of wood will suffice for the sill logs, provided it is sound throughout. However, it is very important that the anticipated life-span of the road be well thought-out. If there is a good chance that the life of the road will be extended, design and construct a culvert with a longer service-life.

The expected service life for sill logs is as follows (subject to site-specific soil and climatic conditions):

- Cedar (sound, with preservatives applied to cut surfaces): 20 years plus;
- Douglas-fir: 8-10 years;
- Spruce, hemlock and balsam: 4-6 years; and
- Hardwood species: Variable but assume it is less than four (4) years.

Table 3-9 Log culvert stringer sizing table--log diameters are middiameters in millimetres

SPAN (metres)	TOTAL FILL DEPTH (metres)	L75 D. Fir	L75 Other	L100 D. Fir	L100 Other	L165 D. Fir	L165 Other
1.5	0.3	250	275	250	325	350	450
	1.0	250	225	225	250	250	300
	2.0	250	250	250	250	250	275
3.0	0.3	375	475	400	475	650	800
	1.0	275	300	275	325	350	400
	2.0	275	325	300	350	375	450
4.5	0.3	500	625	575	675	700	825
	1.0	350	425	375	475	500	600
	2.0	400	475	425	475	525	625
5.9	0.3	600	725	650	775	800	950
	1.0	450	550	500	575	600	750
	2.0	500	625	525	650	625	825

Notes Table 3-9:

1. Other refers to cedar, spruce, lodgepole pine, Jack pine, and hemlock.

- 2. Sizes are based on sound logs, with no allowance for decay.
- 3. Logs should be free of cracks, excessive taper, sweep, damage, or large knots.
- 4. Reverse the taper of adjacent logs.
- 5. Spans over 3 m should be lashed at mid-span.
- 6. Logging truck axle loads in accordance with B.C. Ministry of Forests, Lands and Natural Resource Operations standards.
- 7. Axle loads allow for unbalanced 60%-40% wheel loading.
- 8. Ensure that fill depths greater than 2 metres are designed by a Professional Engineer, or designed from tables prepared by a Professional Engineer.

Mud Sills

If the natural ground will not support the culvert loads on a single sill log, increase the load-bearing area with the use of mud sills. These are short logs, 250 mm (or larger) in diameter, and 1 to 6 m in length, placed at right angles under the sill log for the entire length of the sill.

For crossings on soft ground, on non-fish bearing streams, another option is to extend the mudsills completely across the channel to and beneath the other sill log. This increases the stability of the structure. It is important that the mudsills be placed below the scour level.

Log Culvert Inlet and Outlet Protection

Where the sill logs for log culverts are placed outside the stream channel and bedded below scour level, do not provide for additional inlet and outlet protection. If there is a concern about erosion around the inlet or outlet, protect any erodible surfaces with rock to a level equivalent to the design flood. Provide at some sites an individually designed settling or debris catchment basin at the inlet.

Inlet Protection for Cross-Drain Log Culverts

Inlet protection for cross-drain log culverts will normally be achieved with a ditch block to ensure that ditchwater is directed into the log culvert and not past it. In most cases, use a catch basin to trap sediment and debris. For cross-drain culverts on a steep road grade, consider lining the ditch block, catchment basin, and the bottom of the channel with rock to minimize scouring.

Outlet Protection for Cross-Drain Log Culverts

Do not consider placing log culverts on top of erodible fills. Direct ditch flows onto erosion-resistant areas or onto outlet protection such as flumes or riprap aprons. Do not direct ditch water flows onto unprotected sidecast material unless it is composed of rock or other erosion-resistant materials. On steeper slopes, erosion control at the culvert outlet is a design challenge. One option is to provide extensive outlet protection down the slope to an erosion-free area.



			CUTBLO	CUTBLOCK IDENTIFICATION		
Licence: K2	K2D/AVCF	Cutting Permit: 009		Block: TS2	Timber Mark K2D009	FDU: B (Taylor)
Silviculture System: Retention	Retention	Opening Number: 92F.024		Location: Klitsa Trail	Lattitude: 49° 16' 32"	Longitude: 125°20' 01"
TAUP(ha): 13.3		NAR (ha): 9.9	<u>K</u>	Retention (ha): 2.3	NP UNN (ha /%): 1.1	P.A.S. Limit (%): 8.5
Road Name	S	Section		Length	Location	tion
TA568	2+205 Case 1 R	2+209 to 3+099 Case 1 Reconstruction		890 m		
TA568G	0+000 New C	0+000 to 0+063 New Construction		63 m	ŀ	
TA568	0+000 New C	0+000 to 0+888 New Construction		888 m	laylor	101
ТА568Н	0+00C New C	0+000 to 0+099 New Construction		ш 66		


			SOIL DISTURBANCE		
ns		Compaction	Displacement	Surface Erosion	Soil Disturbance Limit (%)
_		High	Very High	High	5
2		High	Moderate	High	2
COMMENTS	The block has a helicopter	nas been designed for a heli r drop zone. The road surfa	The block has been designed for a helicopter & cable yarding harvest system. The existing road TA568 will be used a helicopter drop zone. The road surface and R/W may be used for landing wood.	est system. The existing ror landing wood.	ad TA568 will be used
	Use puncheon or ricannot be avoided:	neon or rubber matting in se	Use puncheon or rubber matting in sensitive areas and stop work if the following soil disturbances annot be avoided:	if the following soil distu	ırbances
	>Wheel/Tra	>Wheel/Track Ruts, Compacted Areas, Gouges, Scalps<	s, Gouges, Scalps<		
	Rehabilitate avoiding sc Wide gouge	e compacted areas and roarabs larger than 1.5 x 1.5 m e and wide scalp are not co	Rehabilitate compacted areas and roadsides by de-compacting with hoe (preferably grapple attachment) while avoiding scalps larger than $1.5 \times 1.5 \mathrm{m}$. Grass seed exposed mineral soil within 1 year of completion of harvest. Wide gouge and wide scalp are not countable soil disturbance categories in de-stumping areas	h hoe (preferably grapple arel soil within 1 year of con agories in de-stumping area	uttachment) while npletion of harvest.
	Soil displac	Soil displacement is VERY HIGH due to the steep slopes.	to the steep slopes.		
	Maximum r	Maximum roadside soil disturbance =25%	.5%		




		RESULTS & STRATEGIES
RESULT OR STRATEGY		HOW THE STRATEGY OR RESULT APPLIES TO THE SITE
	•	The proposed harvest area is within the Sproat Lake Landscape Unit where OGMAs were established on July 18, 2005.
5.1.1a Order Establishing	•	OGMA NAN_splk_54 is located directly adjacent to the proposed harvest area but does not encroach onto it. OGMA NAN_splk_11 is located to the west of the proposed harvest area.
Sproat Lake Landscape Unit and Objective – Objective 1: Old Growth		Permissible activities that may occur for NAN_splk_54 include: removal of danger trees, or brushing and clearing within the right-of-way on existing
Management Areas (OGMAs)		
	•	No replacement OGMA is needed since there are no known OGMA infringements.
	•	The proposed harvest area is within the Sproat Lake Landscape Unit.
5 1 1h Order Establishing	•	A 1.1 ha (8.2%) WTRA (based on TAUP) has been retained adjacent to the block, meeting minimum requirements set out in the approved Sproat Lake Landscape Unit Plan for areas within the CWH mm (7%) amd CWH vm (5%) BEC subzones. This WTRA contains old growth Hw, Fdc Cw, representative of the pre-harvest stand.
Sproat Lake Landscape Unit and Objective – Objective 2: Wildlife Tree	•	AVCF will ensure that the 5 year average of WTRA will met the minimum requirements set out in the approved landscape unit plan for areas within the CWH mm & CWH vm BEC subzones by ensuring that each individual block meets this target.
Retention (WTR)	•	AVCF will ensure that the WTRA are distributed across the landscape by ensure that each WTRA is directly adjacent to their corresponding cutblock, which is planned to be distributed across the license area. Permissible activities that may occur for this WTRA include: Removal of danger trees, WTRAs with a high likelihood of windthrow may be pruned or topped to maintain the integrity of the WTRAs.
	•	The proposed harvest area is within SMZ 17 of the Sproat Lake Landscape Unit
5.1.1b Order Establishing Sproat Lake Landscape Unit and Objective – Objective 3: Special Manadement Zone 17	•	Sustain forest ecosystem structure and function within the portion of Special Management Zone 17 located in the Sproat Lake Landscape Unit, by retaining mature and old forests (i.e. >80 years of age) on an area covering at least 25 per cent of the total forested area of the SMZ portion located within the landscape unit.
(SMZ 17)	•	The strategy is consistent with AVCF Management Plan objectives and strategies for landscape level biodiversity (S 13.3.9.2).
5.1.2a Vancouver Island Land Use Plan Higher	•	The proposed harvest area is within SMZ 17.
Level Plan Order – Objective 1a: Sustain forest ecosystem structure	•	Sustaining forest ecosystem structure and function in SMZ 17 as per VILUP Objective 1a) will be managed as per the strategy for Objective 3 of the Sproat Lake Landscape Unit Plan, included in section 5.1.1 of the FSP.



and fination in CMZs		
5.1.2b Vancouver Island Land Use Plan Higher Level Plan Order – Objective 1b: Sustain forest ecosystem structure and function in SMZs.	• •	The proposed harvest area is within SMZ 17. The proposed harvest area is designed in a manner that is consistent with retaining structural forest attributes and elements with important biodiversity functions that exist in the established WTRA and Timbered Leave Areas (TLA). These retention areas contain old growth HwFdcCw, representative of the pre-harvest stand and will maintain functional biodiversity within the retained forest.
5.1.2c Vancouver Island Land Use Plan Higher Level Plan Order – Objective 1c: Sustain forest ecosystem structure and function in SMZs.	•	The proposed harvest area is within SMZ 17 where a retention silviculture system is required for cutblock (harvest) areas greater than 5 ha. The NAR of the proposed harvest area is 9.9 ha over three separate polygons. The southern polygon (6 ha) will be harvested using a retention silviculture system where a retention system is defined as retaining "individual trees or groups of trees to maintain structural diversity over the area of the cutblock for at least one rotation" and to maintain > 50% Forest Influence. Pre-marked individual and small groups of trees are to be reserved from harvest in the southern polygon and must be representative of the existing stand, dominant or co-dominant, and be of good form and vigour. The Forest Influence criteria has been achieved at a total of 64%.
5.1.2d Vancouver Island Land Use Plan Higher Level Plan Order – Objective 2.	•	The proposed harvest area is within SMZ 17, however this objective is not applicable since this block is not intended to to recover timber damaged by fire, insects, wind or other similar events.
5.2.1 Soils (FPPR s.35-36)	• •	Soil disturbance limits comply with Section 35 & 36 of the FPPR. Limits are listed in SOIL DISTURBANCE section of the Site Plan. Permanent access structures comply with Section 36 of the FPPR. Permanent access structures structures for the development are 8.5%. The area occupied by permanent access structures exceeds 7% due to the size, topography and engineering constraints of the cutblock and safety of road users. The permanent access structure limit is exceeded by as little as practicable.
5.2.2 Wildlife – MAMU (FPPR s.7)	•	The cutblock will not affect Class 1, 2 or 3 Marbled Murrelet (MAMU) habitat in the non-contributing landbase. There are no Wildlife Habitat Areas (WHA) for MAMU within the immediate vicinity of the cutblock.
5.2.3 Water, Fish, Wildlife and Biodiversity within Riparian Areas (FPPR s.47-52)	• •	For each riparian class of stream found in and adjacent to the harvest area, the minimum riparian management area (RMA) width, riparian reserve zone (RRZ) width and riparian management zone (RMZ) width, on each side of the stream, are as per the table in FPPR 47(4). There are no wetlands or lakes, in or adjacent to the harvest area.



	•	The proposed harvest area is within the Sproat Lake Community Watershed.
5.2.4 Community Watersheds (FPPR s.8.2)	•	The recent CWAP "Sproat Lake Watershed Assessment Update Final Report" by Warren Cooper RPF (March 22, 2013) reported an Equivalent Clearcut Area (ECA) of 13% for the Sutton sub-basin. As per the FSP Subsection 1, in respect of FPPR S 8, the AVCFC will adopt as a result/strategy FPPR S 59 (protecting water quality), S 60 (licensed water works) and S 61 (excavated or bladed trails).
	•	CWAP recommendations have been followed and assessments completed to ensure low to moderate material adverse hydrological effects will occur as a result of forest practices.
5.2.5 Wildlife and Biodiversity – Landscape Level (FPPR s.64-65)	•	The NAR is less than 40 ha (9.9ha) and is not considered adjacent to any existing non-greened up cutblocks. This is in accordance with the result or strategy adopted by the FSP and FPPR Sections 64 & 65 with respect to maximum cutblock size and adjacency.
5.2.6 Wildlife and Biodiversity – Stand Level (FPPR s.66-67)	• •	Wildlife tree retention targets are in accordance with the results or strategy for the approved Sproat Lake Landscape Unit Plan Objective 2. (FSP s. 5.1.1b) No signs of bear dens were observed during field work.
5.2.7 Cultural Heritage Resources (FPPR s.10)	• •	The proposed cutblock is located in the asserted traditional territory of the Hupacasath and Tseshaht First Nations. AVCFC, as the holder of the FSP under which this cutblock is subject to, is solely responsible for First Nations consultation and must be completed prior to Cutting Permit advertisement/award. If, during harvesting, any evidence of traditional use or cultural heritage values is found notify the AVCF Manager and the Ministry of Forests Aboriginal Liaison Officer and cease work within a 30m radius of the area.
5.3.1 Visual Quality Objectives (FPPR s.7 – GAR Order)	•	The development area overlaps with a polygon with Visual Quality Objective of Partial Retention. A Visual Impact Assessment completed by Olak Visuals in October 2015, shows that the development will remain within the required visual quality objective for the area.



		Acceptable Species				Crop Tree to Brush	Ratio %)	150		150
			HW	2 Ba		Ht. by ies	Ht (m)	2.0 1.5 3.0		2.25 1.0 1.0 1.75 1.25
	0	Preferred Species	Cw Fd	Fd ¹⁰ Cw Hm ¹² Yc Hw		Min. FG Ht. by Species	Species	H CW		Fd Hw Cw Yc Hm
	17 - 17 - N M - 71	Kegeneration Method	Plant	Plant		MSSp	(yds)	400		400
מחסעם	- APL	_	25			MSSp	(yds)	200	,	500
STOCKING STANDABLE	NG O DN	Site Series	015003250525	01750325					er e	
CTOCKI	al OCRI	Variant S	0	2	Trial Use	TSS	(yds)	006		006
	L	Subzone Variant Site Series	шш	шш	Restricted to	MITD	(m)	2.0		2.0
		Zone	CWH	CWH	ts. (¹⁸) F			,	5	-
		(ha)	7.2	2.7	herly aspec	FG Date Late	(yrs)	7		-
	CI - F	Standards ID	1028537	1028545	(10) Restricted to southerly aspects. (18) Restricted to Trial Use	Regen. Date	(yrs)	9	*	Q
	-	90	, -	2	(¹⁰) Res	ns	0	_		2



CRITICAL FACTORS AND REGENERATION COMMENTS

Harvesting: Block boundaries are established with orange flagging, orange tags, and falling corners. Boundary trees may be harvested when they are adjacent to an existing road or block. All other boundary trees should not be felled or damaged

A windthrow assessment was completed by Meridian Forest Services in August 2015. Block TS2 has been assessed as having a LOW windthrow risk. The windward edges of cutblock TS2 are mostly sheltered by bluffs controlling the upper boundary line. Remaining timber along the windward edges will experience minimal windthrow well within the acceptable level of damage (10-70%) No windfirming treatment is required. within 1 tree length). Windthrow:

Terrain Stability: A final Terrain Stability Report was completed by Jack Whittles, P.Geo, in September 2015. The proposed cutblock was assessed as having VERY LOW to LOW likelihood for post-harvest landslides with the exception of two terrain units with a moderate risk of post harvest landslides. Three sections of along proposed Road TA568 will required Full Bench Endhaul to reduce the potential for Fillslope failures to LOW. No boundary changes were required. Workers should be made aware of the extreme potential for rockfall to occur from directly upslope of this area.

Recreation: The southwest boundary of the largest polygon borders an unmaintained hiking trail with access to Mt Adder. The majority of the trail is located outside TS2 within the existing cutblock and the legal OGMA. However, there is approximately 100 m of trail is located within the proposed cutblock. Harvesting will not impact recreational opportunities since the maintained Mt Adder Trail has been re-located to the east with access through TS1.


Endemic spot infections may exist Root Rot: No significant root rot infection centres were identified in this block during fieldwork. but no treatment is prescribed. As per FPPR section 68, retain a minimum of Coarse Woody Debris: Coarse woody debris will be left on site to meet biodiversity targets. 4 logs/ha each being at least 5m in length and 30 cm in diameter at one end

This is equivalent to 8.1% of the TAUP and is Wildlife Tree Retention Areas: A WTRA totaling 1.1 ha has been designated for TS2. located between FC 28 to FC 32 within the legal OGMA (NAN_splk_54).

Invasive Plants: Follow FSP measures for invasive plants. Cut and remove plants in association with road reactivation, clean machinery as required. Monitor and treat broom and other invasive species during early establishment. Grass seed exposed soil on or adjacent to roads, trails, and landing sites as soon as possible following harvest.

Natural Range Barriers: Natural range barriers do not apply to the proposed harvest area

Regeneration: Plant promptly following harvesting to minimize the potential need for future brushing treatments. Focus Cw on water receiving sites. Block TS2 has a low brush competition hazard.



Recommended Planting Prescription:

A CONTRACTOR OF		-	*****		-	Mary Ton
Total Stems	5040	2160	540	1620	540	
Stems/ha	200	300	200	009	200	
Stock Type	315A or smallest	available	315A or smallest	available		
Percent (%)	70		20	09	20	
Species	Fd	Cw	Yc	Ba	Cw	
NAR (ha)	7.2		2.7			
SU	_	2	2			

A more detailed planting prescription is to be completed during the Post-Harvest Assessment.

			RIPARIAN MANAGEMENT	
Riparian ID	Riparian Class	Riparian Reserve Zone Width (m)	Riparian Management Zone Width (m)	Riparian Prescription
_	S4	0	30	FA/YA/NX/NC
က	S2	30	20	FA/YA/NX/NC
4R1	S3	20	20	FA/YA/NX/NC
4R2	S4	0	30	FX/YA/NX/NC
4A	NCD	0	0	FX/YX/NX/NC
4B	S4	0	30	FX/YX/NX/NC
4C	S4	0	30	FX/YX/NX/NC
5	S3	20	20	FA/YX/NX/NC
9	S4	0	20	FA/YX/NX/NC

The proposed cutblock TS2 is located within the Sproat Community Watershed, where all streams within and surrounding the proposed cutblock are classified as non-fish S2, S3 or S4 streams as per the Forest Planning and Practices Regulation (FPPR) s. 47(2). However, provided a written rationale prepared by a qualified professional considers the Factors in Schedule 1, Section 2 of the FPPR, a variance to harvesting within the RMAs is permitted. The proposed cutblock is located approximately 1.5 km upstream from Sutton Creek, which drains into the Taylor River which eventually enters Taylor Arm at the western most point in the watershed. The nearest licensed waterworks feature is located on the eastern side of Sproat Lake. Therefore, the role played by trees and understory vegetation in conserving water quality and the need to maintain stream bank and stream channel integrity, and the relative importance and sensitivity of different riparian classes of streams is VERY LOW considering the remoteness of the streams in relation to Sproat Lake and the high level and are not expected to affect the water quality of any of the streams. All streams are not temperature sensitive and therefore, are not to play a role in forest shading. Therefore, The RMA rationale for cutblock TS2 is considered to be consistent with the requirements of the Alberni Valley Community Forest Stewardship Plan 2011-2016, Section 5.2.3 and the Factors listed under FPPR Schedule 1 Section 2. A Riparian Assessment was completed by Meridian Forest Services Ltd. in September 2015. These Riparian Management Strategies are consistent with FPPR S 47 to S 58. of lake buffering to the nearest waterworks feature. The harvest activities are anticipated to be relatively short lived, be of low intensity,

Definitions:

FX: Fall across acceptable.
FA: Fall Away only. Timber is YA: Yard Away. Timber is to YX: Yard Across acceptable.
NC: No stream cleaning requ


Timber is to be felled away from the stream


Yard Away. Timber is to be yarded away. Yard Across acceptable. Follow Y & L SOP


No stream cleaning required.





	RPF SIGN	RPF SIGNATURE AND SEAL
Signing RPF:	Donna Underwood RPF #3136	OF CONTROL
	RPF Name (Printed)	BRITISH
Date Signed (dd/mm/yyyy)	07/06/2016	RPF Signature and Seat 0 + 106/16
N.		
"I certify that the wor	k described herein fulfills the standards e	I certify that the work described herein fulfills the standards expected of a member of the Association of British Columbia Forest
Professionals and the	Professionals and that I did personally supervise the work."	





























Safety Highlights – OPENING#TS2

ACCESS ROAD: TA568 CUTTING PERMIT: NO. 9 TIMBERMARK: K2D 009

STEEP ROAD GRADES

Road segments with gradients > 18% have been identified on the Harvest and Road Instruction Plan Map in and en route to the setting, they are as follows:

TA568J

- 130-156m
- 164-232m
- 264-276m
- 318-333m
- 433-480m
- 499-523m
- 648-677m
- 703-770m
- 820-856m

Prior to commencing log hauling operations the contractor must perform a risk assessment of the current conditions and adjust hauling activities to fit the traction conditions. Hauling for TS2 will not be permitted when ice and or snow is on the logging roads leading to or in the given setting (very low traction level). This has been determined using FERRIC step grade decent guidelines. The Ministry of Transportation guidelines are to be followed once hauling on the highway.

ROCK FALL HAZARD

Rock fall hazards have been identified in two areas of cutblock TS2. Area one is below the bluffs from FC 10 to FC#12 and from FC#5 to FC#6. Area two is along the base of the rock outcrops near FC#29, just east of the NCD. A more detailed description of these areas can be found on in the Terrain Stability Assessment Report. The areas may also be viewed on the harvest and road instructions map.

RAINFALL SHUT DOWN


Cutblock TS2 is within Rainfall Shutdown Area "5"

Shutdown Criteria: Activities must shut down if: The total rainfall reaches 72 mm in 24 hours. Onsite rain gages should be used and monitored daily. **Start-Up Criteria**: Activities may start-up when: The total rainfall is equal to or less than 50 mm in 48 hours. Refer to the Return to work guide in the tender document for more information.

Adequate recovery time should be given before building operations commence after a shutdown.

FALLING of SNAGS and DANGER TREES

There are minimal snags and danger trees within cutblock TS2. The following instructing area to be followed if dealing with snags and danger trees: In accordance with the Cutting Permit Authority and Work Safe BC Regulations, all snags and danger trees that endanger workers within a distance of 50m outside the cutblock boundaries, or within one and a half tree lengths, (whichever is greater), are approved for falling under these harvest



Safety Highlights – OPENING#TS2

instructions. All danger trees and snags outside the cutblock boundaries that are required to be felled must be recorded on a map and provided to AVCF once falling has been completed. AVCF will be notified immediately if danger trees and/or snags are identified in groups and removal will result in the cutblock boundary being substantially impacted. Felled snags and danger trees up to 50m outside of the falling boundary meeting utilization specifications will be recovered.

EXCEPTION- Wildlife Tree Patch (WTP) areas and OLD Growth Management Areas (OGMAs) - Snags or danger trees can be felled within a WTP for safety reasons although only the portion of the felled snag or danger tree that falls outside the WTP can be recovered.

Steep Slopes

This setting is to be hand felled and logged utilizing both grapple yarding and helicopter harvest systems. Operators are to assess areas prior to operation.

Recreational Use


Cutblock TS2 can be accessed from the public. Adequate signs must be posted to inform public of active blasting, logging, and hauling of the area.

Leave Trees

Uniformly dispersed leave trees have been retained within the harvest areas as part of the **legal requirements** for cutblock's located within the Sproat Lake Special Management Zone No. 17. As such, these trees have been selected and marked /identified with a blue panted "L" for leave tree. They are not to be cut or damaged during cutblock development.

Wet Weather Shutdown (modified Nov 7, 2006)





5	4	သ	2			Zone
3500	3000	2500	1500	750	Precip (mm)	Mean Annual
90	75	60	40	20	(mm/24 hours)	Shutdown Threshold

Very Erodible (e.g.	Multiplier Factor
Very Erodible (e.g. lacustrine)	0.4
Erodible (e.g. organics, sands)	0.6
Least Erodible (e.g. colluvium, till)	0.8
Bedrock	1.0

Instructions:	89% +	71% - 88%	57% - 70%	0% - 57	TABLE C Slope Modifier Multiplier Factor
	0.7	0.8	0.9	1.0	ier

- Use base shutdown threshold from Table A
- Multiply by Soil Type Modifier from Table B
- Multiply result by Slope Modifier from Table C

Result is rainfall shutdown threshold in millimeters in a 24 hour period

Example

ı
Table-A:-Mean-Annual-¤



The second secon	Bedrocka	Least·Erodible·(e.g.· colluvium,·till)¤	Erodible (e.g. organics, sands)	Very-Erodible-(e.g lacustrine)¤	в	TABLE-B-Local-Soil-Typen
	1.0¤	0.8н	0.6н	0.4п	Factors	Multipliens



0.7m	0.8п	0.9п	1.0¤	Factor	fiera Multipliera
89%-+□	71%88%□	-57%70%¤	0%57¤	å	TABLE-C-Slope-Modifiera

For Dark Blue Zone 5; 24 Hr Shutdown Criteria = 90 x 0.8 x 0.8 = 58 mm


Return to Work Estimation Guide

Water balance returns to normal after a heavy rainfall period subject to a number of variables

- slope position
- -slope gradient
- soil type and depth (or proximity to bedrock)

Where a road is located above the worksite, interception by ditch lines may have the effect of increasing the recovery rate for lower slope

In an average situation precipitation input is reduced in a 24 hour period by the indicated values based on slope position Using the following sketch as a guide, identify the slope position of the planned activity (upper, middle and lower thirds)



ALBERNI VALLEY COM FOREST

000 - CP# 00

Mount Taylor Block #: CB TS2

SUMMARY OF VOLUMES (CGNF)
FULL VOLUMES APPLIED

04-Nov-2015 02:42:44PM



*** FOR MPS PURPOSES ***

Map Area Statement Report

MAS- 1 , p2 04-Nov-2015 02:42:44PM

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

FIZ: B PSYU: Quadra Region: 2 - West Coast District: 04 - South Island 04-NOV-2015 02-42-44FM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Card A Cruise Ide	entity
-------------------	--------

: 000 : 1 : South Island Licence # Number of Blocks Forest District Unit No Cutting Permit # Forest Region : 00 West Coast : PSYU : Woodlot Licences (COAST) : None Type Tenure Quadra Prop./Mngd.PSYU,TFL,or SSA

Quota Elevation Sale Type Co-ordinates Zone Unknown East Total Merch Area North

: 0
: *** FOR MPS PURPOSES *** Report Type 9.90 Locality : Mount Taylor

Card B Compilation Standard

Selective : Compile All Trees
Special Compilation : No Special Compilation
Type of Compilation : Coastal Damage Double Sampling : Damage : Measure Plots Only Species Compilation : Exceptions Not Used

Compilation Standard Mature Immature Stump Height Top Diameter 30 10.00 15.00

Card C Type Description

		Silvicultural Treatment Units
Type	Description	A
1	FdHw (BaCy)	0.5
2	FdHw(CyCwBa)	1.7
3	HwFd(BaCyCw)	7.7

Card D Block Description

					Silvicultural Treatment Units
Block	Description	Maturity	Type	A	
			_		
001	CB TS2	M	1	0.5	
			2	1.7	
			3	7 7	

Card F Harvesting Description

cara r ma	resering Description			
Harvest	Harvest			Silvicultural Treatment Units
Method	Description	Type	A	
CC	Cable - Clearcut	2	0.4	
HL	Heli - Land	2	1.3	
		3	0.5	
SC	Ground Systems - Clearcut	1	0.5	
	•	3	7.2	

Card G Treatment Unit Description Treatment Unit Description

FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage,

omp Copyright@ 1996-2013, Industrial Forestry Service Ltd

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

*** FOR MPS PURPOSES *** DSF- 1 , p3 04-Nov-2015 02:42:44PM

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

Double Sampling Factors
FIZ: B
PSYU: Quadra
Region: 2 - West Coast
District: 04 - South Island

04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

	F	C	H	В	YC
Utilization Limits					
Min DBH cm (M)	17.5	17.5	17.5	17.5	17.5
Stump Ht cm (M)	30.0	30.0	30.0	30.0	30.0
Top Dia cm (M)	15.0	15.0	15.0	15.0	15.0
Log Len m	13.0	13.0	13.0	13.0	13.0
Type Factors					
Forest Types:					
1 :FdHw (BaCy)	1.0000	1.0000	1.0000	1.0000	1.0000
2 :FdHw(CyCwBa)	1.0000	1.0000	1.0000	1.0000	1.0000
3 :HwFd(BaCyCw)	1.0000	1.0000	1.0000	1.0000	1.0000
3 · Hwrd(Bacycw)	1.0000	1.0000	1.0000	1.0000	1.0000
Block Factors					
Block 001:					
Forest Types:					
1 :FdHw (BaCy)	1.0000	1.0000	1.0000	1.0000	1.0000
2 :FdHw(CyCwBa)	1.0000	1.0000	1.0000	1.0000	1.0000
3 : HwFd(BaCyCw)	1.0000	1.0000	1.0000	1.0000	1.0000
Harvest Method Factors					
Method: CC: Cable - Clearcu Forest Types:	t				
1 :FdHw (BaCy)	1.0000	1.0000	1.0000	1.0000	1.0000
2 : FdHw(CyCwBa)	1.0000	1.0000	1.0000	1.0000	1.0000
3 :HwFd(BaCyCw)	1.0000	1.0000	1.0000	1.0000	1.0000
5 · Hwr a (Bacy cw)	1.0000	1.0000	1.0000	1.0000	1.0000
Method: HL: Heli - Land Forest Types:					
1 :FdHw (BaCy)	1.0000	1.0000	1.0000	1.0000	1.0000
2 :FdHw(CyCwBa)	1.0000	1.0000	1.0000	1.0000	1.0000
3 :HwFd(BaCyCw)	1.0000	1.0000	1.0000	1.0000	1.0000
5 Inita(Ede)(iii)	1.0000	1.0000	1.0000	1.0000	1.0000
Method: SC: Ground Systems Forest Types:	- Clearcut				
1 :FdHw (BaCy)	1.0000	1.0000	1.0000	1.0000	1.0000
2 :FdHw(CyCwBa)	1.0000	1.0000	1.0000	1.0000	1.0000
3 :HwFd(BaCyCw)	1.0000	1.0000	1.0000	1.0000	1.0000
J · HWI a (Dacy CW)	1.0000	1.0000	1.0000	1.0000	1.0000

FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, ${\it CruiseComp~Copyright@~1996-2013,~Industrial~Forestry~Service~Ltd.}$

*** FOR MPS PURPOSES *** APPSM- 1 , p4 Appraisal Summary Report

12643

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2 Location: Mount Taylor

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table No Of Blocks: 1

10.0

FIZ: B PSYU: Quadra Region: 2 - West Coast District: 04 - South Island

04-Nov-2015 02:42:44PM 04-NOV-2015 02-42-44FM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Utilization Levels: Minimum DBH Top Diameter Stump Height Mature Blocks: (cm)

12.0

Standard Log Length:(m) 13.00

Net Area: [All Treatment Units: 9.9]

Immature Blocks:(cm)

All Method Summary
Cruiser Call Variable Length Grades %
Species B C D I J U X Net Volume (m3) Net Volume / ha Species
Code Description
BA Balsam
CE Cedar
CY Y. Cedar
FI Doug-Fir Live 173.571 37.919 71.305 469.863 A11 Live 1718 A11 DΡ 0 173.571 88 46.774 0 71.305 0 469.863 8 50 7 13 39 1718 463 0.000 375 8.854 23 17 41 3 16 36 25 1 7 706 4652 706 4652 0 0.000 FI Doug-Fir HE Hemlock Total 2 7 38 20 22 5191 12730 524.393 1277.051 0.000 5191 0 524.393

Harvesting Method Summaries

	**	37.1 77.7	37.1 77.7		B 11 1	63		
	Net	Net Vol	Net Vol	Hem+	Partial	Slope%	Down	Heavy
Harvest Method	Volume	/10m Log	/Hectare	Bal%	Cut%		Tree%	Fire%
		_						
CC	944	1.54	2359.764	20		108	2	0
HL	3614	1.56	2007.925	28		53	2	0
SC	8172	1.64	1061.337	70		78	0	0
Conventional Methods	9116	1.63	1125.457	65		80	0	0
All Methods	12730	1.61	1285.905	54			1	0

Cutting Authority

95% Confidence Interval	26.9			
Plots/Ha	1.2			
Cruised Trees/Plot	5.5			
Net 2nd Growth-Conifer %	0.0			
Net 2nd Growth-Conifer (m3)	0			
Net Immature by Block %	001: 0%			
Non Heli Select Conifer (m3/ha)	1285.91			
Heli Select Total (decimal)	0.00			
Heli+Skyline Total (decimal)	0.28			
Piece Size - Conifer (m3/10m log)	1.61			
Cruise Date (yy-mm):	15-11			
# Plots: 12 # <= 5yrs: 12	# > 5yrs:	0 # > 10yrs:	0 # no date:	0

FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage,

*** FOR MPS PURPOSES ***

AHV- 1 , p5

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2 Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table All Method Summary
FIZ: B
PSYU: Quadra
Region: 2 - West Coast
District: 04 - South Island

04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

[All Treatment Units : 9.9]

		m	Conifer	Decid	Ŧ	C	н	В	YC
Itilization Limits		IOLAI	Confler	Decia	r	C	н	В	YC.
Min DBH cm (M)					17.5	17.5	17.5	17.5	17.5
Stump Ht cm (M)					30.0	30.0	30.0	30.0	30.0
Top Dia cm (M)					15.0	15.0	15.0	15.0	15.0
Log Len m					13.0	13.0	13.0	13.0	13.0
folume and Size Data					13.0	13.0	13.0	13.0	13.0
Gross Merchantable	m3	14390	14390		5108	562	5926	1993	802
Net Merchantable	m3	12730	12730		4652	463	5191	1718	706
Net Merch - All		1285.905			469.863	46.774	524.393	173.571	71.305
		1277.051			469.863	37.919	524.393	173.571	71.305
	m3/ha	8.854	8.854		103.003	8.854	321.333	1/3.3/1	71.505
Net Meren Di	m5/ma	0.031	0.031			0.051			
Decay	%	5	5		2	6	6	8	5
Waste(billing)	%	1	1		1	6	1	0	
Total Cull (DWB)	%	12	12		9	18	12	14	12
Net Merch Vol/Tree	m3	3.43	3.43		11.90	2.38	3.41	1.37	2.03
Avg 13.0 m Log Net	m3	1.61	1.61		3.19	1.21	1.53	0.80	1.34
Useless Dead/Living	%	14	14				29		
Net Second Growth	%								
All Burn Volume	%								
Heavy Fire Volume	%								
Blowdown Volume	%	1	1			19			
Insect Volume	용								
ruiser Call Variable	Lengtl	n Grades	k						
#2 Peeler	В	2	2		5				
#3 Peeler	C	1	1		2				
#1 Lum/#1 Prem	D	2	2		2		2		
#2 Lum/#1 Lum	F	12	12		22		7	10	
#2 Sawlog	H	34	34		36	43	38	24	23
#3 Sawlog	I	20	20		25	13	20	8	17
#4 Sawlog	J	20	20		1	39	22	50	41
	IJ	4	4				6	7	3
#5 Utility	U								
#5 Utility #6 Utility	X		-			5			

^{*** 1} tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, cruiseComp Copyrightto 1996-2013, Industrial Forestry Service Ltd.

Harvest Method Summary

Average Line Method Grades: Cruiser Called Alpha
ALBERNI VALLEY COM FOREST Cruiser Est Decay
Licence Number: 000 CP: 00 Cruiser Est Waste
Project: TS2 CGNF Breakage Table

FIZ: B
PSYU: Quadra
Region: 2 - West Coast
District: 04 - South Island

04-Nov-2015 02:42:44PM
Filename: cbts2_2015opc_20151104.ccp
Compiled by: Contour Forest Consultants Inc
Cruised by: CONTOUR FOREST CONSULTANTS INC
Version: 2014.00 IFS build 5888

Harvest Method : CC - Cable - Clearcut [All Treatment Units : 0.4]

			- 15		_	_		_	
		Total	Conifer	Decid	F	C	Н	В	YC
Utilization Limits Min DBH cm (M) Stump Ht cm (M) Top Dia cm (M) Log Len m Volume and Size Data					17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0
Gross Merchantable Net Merchantable Net Merch - All Net Merch - Live Net Merch - DP		1052 944 2359.764 2308.201 51.563			636 585 1463.098 1463.098	83 63 157.430 105.867 51.563	163 145 363.389 363.389	50 43 106.884 106.884	121 108 268.963 268.963
Decay Waste(billing) Total Cull (DWB)	වල වල වල	1	4 1 10		2 0 8	10 10 24	5 11	8 14	5 11
Net Merch Vol/Tree Avg 13.0 m Log Net Useless Dead/Living	m3 m3 %	3.34 1.54	3.34 1.54		13.65 3.65	1.59 0.86	1.61 0.86	0.52	3.77
Net Second Growth	%								
All Burn Volume Heavy Fire Volume Blowdown Volume Insect Volume	do do do do	2	2			33			
% Average Slope		108							
Cruiser Call Variable	Lengt	h Grades	*						
#2 Peeler #2 Lum/#1 Lum #2 Sawlog #3 Sawlog	B F H I	3 15 27 26	3 15 27 26		5 24 34 31	33	27		36 26
#4 Sawlog #5 Utility #7 Chipper	J U Y	19 1 9	19 1 9		6	67	53 7 13	100	14 24

^{*** 1} tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyrighto 1996-2013, Industrial Forestry Service Ltd.

*** FOR MPS PURPOSES ***

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

Harvest Method Summary
FIZ: B
PSYU: Quadra
Region: 2 - West Coast
District: 04 - South Island

HV- 2 , p7 04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Harvest Method : HL -	Heli	- Land	[All T	reatment:	Units : 1	.8]					
		Total	Conifer	Decid	F	C	Н	В	YC		
Utilization Limits Min DBH cm (M) Stump Ht cm (M) Top Dia cm (M) Log Len m Volume and Size Data					17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0		
Gross Merchantable Net Merchantable Net Merch - All Net Merch - Live Net Merch - DP		4043 3614 2007.925 1970.685 37.240			2209 2030 1127.626 1127.626	282 217 120.749 83.510 37.240	869 769 427.445 427.445	269 232 128.882 128.882	413 366 203.222 203.222		
Decay Waste(billing) Total Cull (DWB)	90 90 90	4 1 11	_		2 1 8	9 9 23	6 0 11	8 0 14	5 11		
Net Merch Vol/Tree Avg 13.0 m Log Net Useless Dead/Living	m3 m3 %	3.36 1.56 4	3.36 1.56 4		13.37 3.57	1.66 0.90	2.10 1.06 10	0.73 0.40	3.40 1.91		
Net Second Growth	%										
All Burn Volume Heavy Fire Volume Blowdown Volume Insect Volume % Average Slope	do do do do	2 53	2			31					
Cruiser Call Variable Length Grades %											
#2 Peeler #3 Peeler #1 Lum/#1 Prem	B C D	3	3		5		1				
#2 Lum/#1 Lum #2 Sawlog #3 Sawlog	F H I	14 29 25	14 29 25		24 35 30	34 2	3 16 24	5 12 4	35 24		
#4 Sawlog #5 Utility #6 Utility	J U X	19 2	19 2			63	41 6	76 3	18		
#7 Chipper	Y	8	8		6		9		23		

^{*** 1} tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright@ 1996-2013, Industrial Forestry Service Ltd.

HV- 3 , p8

Average Line Method
ALBERNI VALLEY COM FOREST
Licence Number: 000 CP: 00
Project: TS2

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table Harvest Method Summary
FIZ: B
PSYU: Quadra
Region: 2 - West Coast
District: 04 - South Island

04-Nov-2015 02:42:44PM
Filename: cbts2_2015opc_20151104.ccp
Compiled by: Contour Forest Consultants Inc
Cruised by: CONTOUR FOREST CONSULTANTS INC
Version: 2014.00 IFS build 5888

 ${\tt Harvest\ Method}\ :\ {\tt SC\ -\ Ground\ Systems\ -\ Clearcut[All\ Treatment\ Units\ :\ 7.7\quad]}$

							•		
		Total	Conifer	Decid	F	C	H	В	YC
Utilization Limits Min DBH cm (M) Stump Ht cm (M) Top Dia cm (M) Log Len m Volume and Size Data					17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0
Gross Merchantable Net Merchantable Net Merch - All Net Merch - Live Net Merch - DP		9295 8172 1061.337 1061.337			2264 2037 264.504 264.504	197 183 23.732 23.732	4894 4277 555.420 555.420	1674 1444 187.482 187.482	267 233 30.199 30.199
Decay Waste(billing) Total Cull (DWB)	<i>ბ ბ ბ ბ</i>	6 1 12	6 1 12		3 3 10	1 7	6 1 13	8 1 14	6 13
Net Merch Vol/Tree Avg 13.0 m Log Net Useless Dead/Living	m3 m3 %	3.48 1.64 20	3.48 1.64 20		10.38 2.79	7.54 2.69	4.01 1.70 35	1.70 1.03	1.09
Net Second Growth	%								
All Burn Volume Heavy Fire Volume Blowdown Volume Insect Volume	de de de de								
% Average Slope		78							
Cruiser Call Variable									
#2 Peeler #3 Peeler #1 Lum/#1 Prem	B C D	1 1 3	1 1 3		4 4 4		3		
#2 Lum/#1 Lum #2 Sawlog #3 Sawlog	F H I	11 37 17	11 37 17		20 39 17	59 30	8 42 20	11 27 9	
#4 Sawlog #5 Utility #6 Utility	J U X	21 5	21 5		3	11	18 6	44 8	91 9
#7 Chipper	Y	4	4		8		3	1	

^{*** 1} tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyrighto 1996-2013, Industrial Forestry Service Ltd.

Cutting Permit Summary Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2 Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

FIZ: B
FIZ: B
PSYU: Quadra
Region: 2 - West Coast
District: 04 - South Island

CP- 1 , p9 04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Net Area: [A : 9.9] Gross Area: [Harvested : 1.1][WTRA : 1.1][Outside R/ : 0.1][Grand Total : 12.2]

TOBB AFCA: [HAIVEBE		1		Cuebiae it/ · o.	1 11 0101	10 10001	12.2	
		Total	Conifer	Decid F	C	Н	В	Y
Jtilization Limits								
Min DBH cm (M)				17.5	17.5	17.5	17.5	17.
Stump Ht cm (M)				30.0	30.0	30.0	30.0	30.
Top Dia cm (M)				15.0	15.0	15.0	15.0	15.
Log Len m				13.0	13.0	13.0	13.0	13.
olume and Size Data								
Gross Merchantable	m3	14390	14390	5108	562	5926	1993	80
Net Merchantable	m3	12730	12730	4652	463	5191	1718	70
Net Merch - All	m3/ha	1286	1286	470	47	524	174	7
Distribution	1113/11a	100	100	37	4 /	41	13	,
Decay	8	5	5	2	6	6	8	
Waste	%	1	1	1	5	1	0	
Waste(billing)	%	1	1	1	6	1	0	
Breakage	%	6	6	5	7	6	6	
Total Cull (DWB)	8	12	12	9	18	12	14	1
Stems/Ha (Live & DP)		374.7	374.7	39.5	19.6	154.0	126.4	35.
Avg DBH (Live & DP)	cm	61.0	61.0	109.1	61.6	60.2	39.6	51.
Snags/Ha		63.2	63.2			63.2		
Avg Snag DBH	cm	17.7	17.7			17.7		
Gross Merch Vol/Tree	m3	3.88	3.88	13.07	2.89	3.89	1.59	2.3
Net Merch Vol/Tree	m3	3.43	3.43	11.90	2.38	3.41	1.37	2.0
Avg Weight Total Ht	m	44.3	44.3	55.5	35.1	40.8	35.5	29.
Avg Weight Merch Ht	m	38.6	38.6	50.4	28.6	33.9	29.5	23.
Avg 13.0 m Log Net	m3	1.61	1.61	3.19	1.21	1.53	0.80	1.3
Avg 13.0 m Log Gross	m3	1.71	1.71	3.32	1.35	1.64	0.87	1.4
Avg # of 13.0 m Logs		2.27	2.27	3.94	2.13	2.37	1.82	1.6
	/iree %	2.21	2.21	3.94	2.13	2.37	1.82	1.0
Net Immature	-							
Net 2nd Growth	8							
Average Slope	%	77						
ruiser Call Variable								
#2 Peeler	В	2	2	5				
#3 Peeler	C	1	1	2				
#1 Lum/#1 Prem	D	2	2	2		2		
#2 Lum/#1 Lum	F	12	12	22		7	10	
#2 Sawlog	H	34	34	36	43	38	24	2
#3 Sawlog	I	20	20	25	13	20	8	1
#4 Sawlog	J	20	20	1	39	22	50	- 4
#5 Utility	Ū	4	4	-		6	7	-
#6 Utility	X	•	-		5	Ŭ	′	
#7 Chipper	Y	5	5	7	3	5	1	1
	1	5	5	,		5	Τ.	1
tatistical Summary	0	41 0	41 0	125.0	161 0	F.C. 0	145.0	٥٢٢
Coeff. of Variation	8	41.2	41.2	135.9	161.7	56.0	145.3	255.
Two Standard Error	8	26.9	26.9	88.7	105.6	36.6	94.9	166.
Number and Type of P.		MP =	12					
Number of Potential ?	Trees	65						
Plots/Ha		1.2						
Cruised Trees/Plot		5.5						

^{*** 1} tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, cruiseComp Copyright© 1996-2013, Industrial Forestry Service Ltd.

BS- 1 , p10

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2 Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

Block Summary
FIZ: B
PSYU: Quadra
Region: 2 - West Coast
District: 04 - South Island

04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Net Area: Block: (M) - 001:CB TS2, Plots in Block: 12, TUs: [A : 9.9]
Gross Area: [Harvested : 1.1][WTRA : 1.1][Outside R/ : 0.1][Grand Total : 12.2]

TOBB AICA: [HAIVEBE	ca . 1.1	JE WIIG	1.1][040	Blue It/ · U.1) Clair	a local .	12.2	
		Total	Conifer Dec	id F	C	Н	В	7
tilization Limits								
Min DBH cm (M)				17.5	17.5	17.5	17.5	17.
Stump Ht cm (M)				30.0	30.0	30.0	30.0	30.
Top Dia cm (M)				15.0	15.0	15.0	15.0	15.
Log Len m				13.0	13.0	13.0	13.0	13.
olume and Size Data								
Gross Merchantable	m3	14390	14390	5108	562	5926	1993	80
Net Merchantable	m3	12730	12730	4652	463	5191	1718	7
Net Merch - All	m3/ha	1286	1286	470	47	524	174	
Distribution	%	100	100	37	4	41	13	
Decay	%	5	5	2	6	6	8	
Waste	%	1	1	1	5	í	0	
Waste(billing)	%	1	1	1	6	1	0	
Breakage	8	6	6	5	7	6	6	
Total Cull (DWB)	*	12	12	9	18	12	14	
Stems/Ha (Live & DP)	-	374.7	374.7	39.5	19.6	154.0	126.4	35
Avg DBH (Live & DP)		61.0	61.0	109.1	61.6	60.2	39.6	51
	cm			109.1	01.0		39.0	2.1
Snags/Ha		63.2	63.2			63.2		
Avg Snag DBH	cm	17.7	17.7	12.05	0.00	17.7	1 50	_
Gross Merch Vol/Tree		3.88	3.88	13.07	2.89	3.89	1.59	2.
Net Merch Vol/Tree	m3	3.43	3.43	11.90	2.38	3.41	1.37	2.
Avg Weight Total Ht	m	44.3	44.3	55.5	35.1	40.8	35.5	29
Avg Weight Merch Ht	m	38.6	38.6	50.4	28.6	33.9	29.5	23
Avg 13.0 m Log Net	m3	1.61	1.61	3.19	1.21	1.53	0.80	1.
Avg 13.0 m Log Gross		1.71	1.71	3.32	1.35	1.64	0.87	1.
Avg # of 13.0 m Logs		2.27	2.27	3.94	2.13	2.37	1.82	1.
Net Immature	%							
Net 2nd Growth	%							
Average Slope	%	77						
ruiser Call Variable	Length Gr							
#2 Peeler	В	2	2	5				
#3 Peeler	C	1	1	2				
#1 Lum/#1 Prem	D	2	2	2		2		
‡2 Lum/#1 Lum	F	12	12	22		7	10	
‡2 Sawlog	H	34	34	36	43	38	24	
‡3 Sawlog	I	20	20	25	13	20	8	
#4 Sawlog	J	20	20	1	39	22	50	
#5 Utility	U	4	4			6	7	
#6 Utility	X				5			
#7 Chipper	Y	5	5	7		5	1	
atistical Summary								
Coeff. of Variation	%	41.2	41.2	135.9	161.7	56.0	145.3	255
Two Standard Error	%	26.9	26.9	88.7	105.6	36.6	94.9	166
Number and Type of P		MP = 1						
Number of Potential		65	-					
Plots/Ha	11000	1.2						
Cruised Trees/Plot		5.5						
lope % Statistics		5.5						
in= 40, Max=113,	CV=32.9,	C+4 P-	ror of Mean=7.	3, 2SE%=20.	۵			
III- TU, MAX-III,	CV-JZ.9,	ocu Er	TOT OF MEAN-/.	J, ZDE7-ZU.	2			

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

04-Nov-2015 02:42:44PM

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

Type Summary
FIZ: B
FSYU: Quadra
Region: 2 - West Coast
District: 04 - South Island

TS- 1 , p11 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Net Area: Type 1 (M):FdHw (BaCy), Plots in Type: 1, TUs: [A : 0.5]

		Total	Conifer	Decid	F	С	Н	В	YC
Utilization Limits									
Min DBH cm (M)					17.5	17.5	17.5	17.5	17.5
Stump Ht cm (M)					30.0	30.0	30.0	30.0	30.0
Top Dia cm (M)					15.0	15.0	15.0	15.0	15.0
Log Len m					13.0	13.0	13.0	13.0	13.0
Volume and Size Data	_								
Gross Merchantable	m3	333	333		214			119	
Net Merchantable	m3	302	302		198			104	
Net Merch - All	m3/ha	603	603		396			208	
Distribution	%	100	100		66			34	
Decay	8	4	4		2			7	
Waste	8								
Waste(billing)	8	_	_		_			_	
Breakage	૪	5	5		5 7			6	
Total Cull (DWB)	%	9	9					13	
Stems/Ha (Live & DP)		193.1	193.1		33.1			160.0	
Avg DBH (Live & DP)	cm	62.9	62.9		124.0			39.9	
Snags/Ha									
Avg Snag DBH Gross Merch Vol/Tree	cm m3	2.45	2 45		12.91			1.49	
Net Merch Vol/Tree	m3 m3	3.45 3.12	3.45 3.12		12.91			1.49	
Avg Weight Total Ht	m m	37.7	37.7		42.6			29.3	
Avg Weight Merch Ht	m	32.9	32.9		38.5			22.2	
Avg 13.0 m Log Net	m3	1.52	1.52		4.20			0.69	
Avg 13.0 m Log Gross		1.52	1.52		4.30			0.74	
Avg # of 13.0 m Logs		2.17	2.17		3.00			2.00	
Net Immature	/ II CC %	2.1/	2.1/		3.00			2.00	
Net 2nd Growth	%								
Nec 2nd Growen	-0								
Cruiser Call Variable	Length	Grades &							
#2 Lum/#1 Lum	F	33	33		50				
#2 Sawlog	H	16	16		25				
#3 Sawlog	I	15	15		22				
#4 Sawlog	J	34	34		22			100	
#7 Chipper	Y	2	2		3			100	
Statistical Summary	-	2	2		3				
Coeff. of Variation	%								
Two Standard Error	%								
Number and Type of P.		MP =	1						
Number of Potential		3							
Plots/Ha		2.0							
Cruised Trees/Plot		3.0							

^{*** 1} tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright0 1996-2013, Industrial Forestry Service Ltd.

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

TS- 2 , p12 Type Summary
FIZ: B
FSYU: Quadra
Region: 2 - West Coast
District: 04 - South Island 04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

Net Area: Type 2 (M):FdHw(CyCwBa), Plots in Type: 2, TUs: [A : 1.7]

			~ 15		_	_			
*************		Total	Conifer	Decid	F	C	H	В	YC
Utilization Limits Min DBH cm (M)					17.5	17.5	17.5	17.5	17.5
					30.0	30.0	30.0	30.0	30.0
Stump Ht cm (M)						15.0	15.0	15.0	15.0
Top Dia cm (M)					15.0				
Log Len m					13.0	13.0	13.0	13.0	13.0
Volume and Size Data		4.450	4.450		0000	254	692	0.1.1	516
Gross Merchantable	m3	4473	4473		2702	351		211	
Net Merchantable	m3	4012	4012		2487	268	618	182	457
Net Merch - All	m3/ha	2360	2360		1463	157	363	107	269
Distribution	%	100	100		62	7	15	5	11
Decay	8	4	4		2	10	5	8	5
Waste	8	1	1		0	8			
Waste(billing)	%	1	1		0	10			
Breakage	%	6	6		5	7	6	6	7
Total Cull (DWB)	%	10	10		8	24	11	14	11
Stems/Ha (Live & DP)		707.2	707.2		107.2	99.1	225.1	204.5	71.3
Avg DBH (Live & DP)	cm	61.9	61.9		115.6	56.7	46.1	27.9	66.8
Snags/Ha									
Avg Snag DBH	cm								
Gross Merch Vol/Tree	m3	3.72	3.72		14.83	2.08	1.81	0.61	4.26
Net Merch Vol/Tree	m3	3.34	3.34		13.65	1.59	1.61	0.52	3.77
Avg Weight Total Ht	m	46.0	46.0		57.1	28.6	30.0	25.0	32.7
Avg Weight Merch Ht	m	40.9	40.9		52.2	21.7	22.7	16.0	26.9
Avg 13.0 m Log Net	m3	1.54	1.54		3.65	0.86	0.86	0.28	2.03
Avg 13.0 m Log Gross	m3	1.62	1.62		3.75	1.04	0.90	0.30	2.13
Avg # of 13.0 m Logs	/Tree	2.30	2.30		3.95	2.00	2.00	2.00	2.00
Net Immature	%								
Net 2nd Growth	ક								
Cruiser Call Variable	Length	Grades %							
#2 Peeler	В	3	3		5				
#2 Lum/#1 Lum	F	15	15		24				
#2 Sawlog	H	27	27		34	33			36
#3 Sawlog	I	26	26		31		27		26
#4 Sawlog	J	19	19			67	53	100	14
#5 Utility	IJ	1	1			0,	7	100	
#7 Chipper	Y	9	9		6		13		24
Statistical Summary	-	-			ŭ				
Coeff. of Variation	%	37.2	37.2		89.3	48.8	49.7	141.4	141.4
Two Standard Error	%	334.5	334.5		802.2	438.3	446.5	1270.6	1270.6
Number and Type of P.		MP =	2		002.2	150.5	110.5	12,0.0	12/0.0
Number of Potential		17	2						
Plots/Ha	11660	1.2							
Cruised Trees/Plot		8.5							
Cruibeu ilees/Plot		0.3							

^{*** 1} tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright0 1996-2013, Industrial Forestry Service Ltd.

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

TS- 3 , p13 04-Nov-2015 02:42:44PM

Type Summary
FIZ: B
FSYU: Quadra
Region: 2 - West Coast
District: 04 - South Island Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Net Area: Type 3 (M):HwFd(BaCyCw), Plots in Type: 9, TUs: [A : 7.7]

		Total	Conifer	Decid	F	C	Н	В	YC
Utilization Limits		IOCAI	CONTLEI	Decia	r	C	11	ь	10
Min DBH cm (M)					17.5	17.5	17.5	17.5	17.5
Stump Ht cm (M)					30.0	30.0	30.0	30.0	30.0
Top Dia cm (M)					15.0	15.0	15.0	15.0	15.0
Log Len m					13.0	13.0	13.0	13.0	13.0
Volume and Size Data					13.0	13.0	13.0	13.0	13.0
Gross Merchantable	m3	9585	9585		2192	210	5234	1663	286
Net Merchantable	m3	8417	8417		1967	195	4574	1433	249
Net Merch - All	m3/ha	1093	1093		255	25	594	186	32
Distribution	%	100	100		23	2	54	17	3
Decay	8	6	6		3	1	6	8	6
Waste	8	1	1		3	1	1	0	0
Waste(billing)	%	1	1		3		1	1	
Breakage	8	6	6		5	7	6	6	7
Total Cull (DWB)	8	12	12		10	7	13	14	13
Stems/Ha (Live & DP)	3	313.1	313.1		25.0	3.4	148.3	107.0	29.5
Avg DBH (Live & DP)	cm	60.5	60.5		101.0	87.0	64.2	43.6	41.6
Snags/Ha	Cili	81.3	81.3		101.0	67.0	81.3	43.0	41.0
Avg Snag DBH	cm	17.7	17.7				17.7		
Gross Merch Vol/Tree	m3	3.98	3.98		11.41	8.12	4.58	2.02	1.26
Net Merch Vol/Tree	m3	3.49	3.49		10.24	7.54	4.01	1.74	1.20
Avg Weight Total Ht	m	43.8	43.8		54.9	46.3	42.2	37.4	23.9
Avg Weight Total At Avg Weight Merch Ht	m	37.7	37.7		49.5	39.0	35.4	31.7	17.7
Avg 13.0 m Log Net	m3	1.64	1.64		2.70	2.69	1.70	1.07	0.83
Avg 13.0 m Log Gross	m3	1.76	1.76		2.84	2.71	1.83	1.17	0.89
Avg # of 13.0 m Logs		2.26	2.26		4.02	3.00	2.50	1.73	1.42
Net Immature	/iree %	2.20	2.20		4.02	3.00	2.50	1./3	1.42
Net 2nd Growth	8								
Net 2nd Growth	6								
Cruiser Call Variable	Length	Grades %							
#2 Peeler	В	1	1		5				
#3 Peeler	C	1	1		4				
#1 Lum/#1 Prem	D	3	3		5		3		
#2 Lum/#1 Lum	F	10	10		17		8	12	
#2 Sawlog	H	39	39		40	59	42	29	
#3 Sawlog	I	17	17		17	30	20	9	
#4 Sawlog	J	20	20		3		18	41	91
#5 Utility	U	5	5		1		6	8	9
#6 Utility	Х					11			
#7 Chipper	Y	4	4		8		3	1	
Statistical Summary									
Coeff. of Variation	ક	38.7	38.7		141.8	300.0	53.2	146.1	300.0
Two Standard Error	ક	29.8	29.8		109.0	230.6	40.9	112.3	230.6
Number and Type of P.	lots	MP =	9						
Number of Potential 7	Trees	45							
Plots/Ha		1.2							
Cruised Trees/Plot		5.1							

^{*** 1} tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, cruiseComp Copyright© 1996-2013, Industrial Forestry Service Ltd.

VLS- 1 , p14 Volume Statistical Analysis 04-Nov-2015 02:42:44PM

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2 FIZ: B PSYU: Quadra Region: 2 - West Coast District: 04 - South Island 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Utilization Levels: Minimum DBH Top Diameter Stump Height

Mature Blocks: (cm)
Immature Blocks:(cm) 17.5 12.0 15.0 10.0

Standard Log Length:(m) 13.00

Plots		Area	Net Volume	Proportional		Trees		Standard	Coeff. of	Samplin	g Error
Cnt Mea	Tot	ha	m3/ha	Volume	Cnt	Mea	Tot	Deviation	Variation	1 SE%	2 SE%
0 1	1	0.5	603.3	0.02	0	3	3	0.0000		0.0	0.0
0 2	2	1.7	2359.8	0.32	0	17	17	878.5699	37.2	26.3	334.5
0 9	9	7.7	1093.1	0.66	0	45	45	423.4374	38.7	12.9	29.8
0 12	12	9.9	1285.9		0	65	65		41.2	11.9	26.9
		Ont Mea Tot 0 1 1 0 2 2 0 9 9	Ont Mea Tot ha 0 1 1 0.5 0 2 2 1.7 0 9 9 7.7	Cnt Mea Tot ha m3/ha 0 1 1 0.5 603.3 0 2 2 1.7 2359.8 0 9 9 7.7 1093.1	Cnt Mea Tot ha m3/ha Volume 0 1 1 0.5 603.3 0.02 0 2 2 1.7 2359.8 0.32 0 9 9 7.7 1093.1 0.66	Cnt Mea Tot ha m3/ha Volume Cnt 0 1 1 0.5 603.3 0.02 0 0 2 2 1.7 2359.8 0.32 0 0 9 9 7.7 1093.1 0.66 0	Cnt Mea Tot ha m3/ha Volume Cnt Mea 0 1 1 0.5 603.3 0.02 0 3 0 2 2 1.7 2359.8 0.32 0 17 0 9 9 7.7 1093.1 0.66 0 45	Cnt Mea Tot ha m3/ha Volume Cnt Mea Tot 0 1 1 0.5 603.3 0.02 0 3 3 0 2 2 1.7 2359.8 0.32 0 17 17	Cnt Mea Tot ha m3/ha Volume Cnt Mea Tot Deviation 0 1 1 0.5 603.3 0.02 0 3 3 0.0000 0 2 2 1.7 2359.8 0.32 0 17 17 878.5699 0 9 9 7.7 1093.1 0.66 0 45 45 423.4374	Cnt Mea Tot ha m3/ha Volume Cnt Mea Tot Deviation Variation 0 1 1 0.5 603.3 0.02 0 3 3 0.0000 0 2 2 1.7 2359.8 0.32 0 17 17 878.5699 37.2 0 9 9 7.7 1093.1 0.66 0 45 45 423.4374 38.7	Cnt Mea Tot ha m3/ha Volume Cnt Mea Tot Deviation Variation 1 SE% 0 1 1 0.5 603.3 0.02 0 3 3 0.0000 0.0 0 2 2 1.7 2359.8 0.32 0 17 17 878.5699 37.2 26.3 0 9 9 7.7 1093.1 0.66 0 45 45 423.4374 38.7 12.9

Number of live & dead potential trees sampled is 65 Number of dead useless trees sampled is 0 Number of live useless trees sampled is 1 $\,$

The weighted sampling error is 26.9% at the 95% confidence level

FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright@ 1996-2013, Industrial Forestry Service Ltd.

BAS- 1 , p15 Basal Area Statistical Analysis 04-Nov-2015 02:42:44PM Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

FIZ: B PSYU: Quadra Region: 2 - West Coast District: 04 - South Island 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Utilization Levels:

Standard Log Length:(m)

Minimum DBH

Top Diameter Stump Height

15.0 10.0

Mature Blocks: (cm)
Immature Blocks:(cm) 17.5 12.0

13.00

Forest	P	lots		Area	Basal Area	Proportional		Trees		Standard	Coeff. of	Samplin	g Error
Type	Cnt	Mea	Tot	ha	m2/ha	Basal Area	Cnt	Mea	Tot	Deviation	Variation	1 SE%	2 SE%
1 :FdHw (BaCy)	0	1	1	0.5	60.0	0.03	0	3	3	0.0000		0.0	0.0
<pre>2 :FdHw(CyCwBa)</pre>	0	2	2	1.7	212.5	0.33	0	17	17	53.0330	25.0	17.6	224.2
3 : HwFd(BaCyCw)	0	9	9	7.7	90.0	0.64	0	45	45	34.8569	38.7	12.9	29.8
TOTAL	0	12	12	9.9	109.5		0	65	65		35.1	10.1	22.9

Number of live & dead potential trees sampled is 65 Number of dead useless trees sampled is 0 Number of live useless trees sampled is 1 $\,$

The weighted sampling error is 22.9% at the 95% confidence level

FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage,

CruiseComp Copyright@ 1996-2013, Industrial Forestry Service Ltd.

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

Cutting Permit Stand Table (stems/ha)

Grades: Cruiser Called Alpha FIZ: B
Cruiser Est Decay PSYU: Quadra
Cruiser Est Waste Region: 2 - West Coast
CGNF Breakage Table District: 04 - South Island

CSTND- 1 , p16 04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

[A : 9.9]

		F	C	H	В	YC	Total	DP	DU	LU
Utilizatio										
Min DBH	cm (M)	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
Stump Ht		30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0
Top Dia	cm (M)	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0
Log Len	m	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0
DBH										
Class										
5										
10										
15										
20										63.2
25					33.0		33.0			
30					35.1		35.1			
35										
40				42.5	31.9	13.3	87.7			
45			12.2	23.1	10.7	9.7	55.6			
50				8.6	7.7		16.3			
55				30.7			30.7			
60				5.4		7.2	12.6			
65				8.9			8.9			
70		4.0		4.3	3.8		12.2			
75				7.3		5.0	12.3	4.9		
80				5.9			5.9			
85			2.6				2.6			
90		2.6		2.3			4.9			
95		3.1		4.4	2.2		9.6			
100		7.6		4.0	2.1		13.8			
105		6.1		3.5			9.6			
110		3.9		1.6			5.5			
115		3.1		1.4			4.6			
120		1.9					1.9			
125		2.9					2.9			
130		2.,					2.,			
135										
140		1.0					1.0			
145		1.0					1.0			
150		2.4					2.4			
175		0.9					0.9			
200		0.5					0.5			
225										
250										
275										
Total		39.5	14.8	154.0	126.4	35.2	369.8			
Dead P		39.3	4.9	134.0	120.4	33.2	309.0	4.9		
Dead V			4.3					4.7		
Live U				63.2						63.2
11 AG 0			λιτο		cm) at 5	l erre l				03.2
12.5 +		109.1	56.5	60.2	39.6	51.8	60.8	75.0		17.7
12.5 + 17.5 +		109.1	56.5	60.2	39.6	51.8	60.8	75.0		17.7
17.5 + 22.5 +		109.1	56.5	60.2	39.6	51.8	60.8	75.0		1/./
27.5 +		109.1	56.5	60.2	43.8	51.8	63.2	75.0		
32.5 +		109.1	56.5	60.2	51.0	51.8	66.1	75.0		

^{*** 1} tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright0 1996-2013, Industrial Forestry Service Ltd.

*** FOR MPS PURPOSES *** CSTCK- 1 , p17 Cutting Permit Stock Table (m3/ha)

Grades: Cruiser Called Alpha FIZ: B
Cruiser Est Decay PSYU: Quadra
Cruiser Est Waste Region: 2 - West Coast
CGNF Breakage Table District: 04 - South Island 04-Nov-2015 02:42:44PM Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

	9 9	

		F	C	H	В	YC	Total	DP	DU	LU
Utilizatio										
Min DBH	cm (M)	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
Stump Ht	cm (M)	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0
Top Dia	cm (M)	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0
Log Len	m	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0
DBH										
Class										
5										
10										
15										
20										
25					8.2		8.2			
30					18.4		18.4			
35										
40				43.5	41.1	11.1	95.7			
45			18.2	35.2	17.8	14.0	85.1			
50				11.6	17.6		29.2			
55				73.4			73.4			
60				17.7		23.2	40.9			
65				38.6			38.6			
70		17.1		17.2	22.6		57.0			
75				35.2		23.0	58.2	8.9		
80				40.6			40.6			
85			19.7				19.7			
90		18.2		20.8			39.0			
95		22.4		53.0	25.8		101.2			
100		73.4		38.7	22.1		134.3			
105		53.5		55.1			108.6			
110		55.9		22.5			78.3			
115		40.2		21.2			61.5			
120		32.8					32.8			
125		42.4					42.4			
130										
135										
140		23.0					23.0			
145										
150		61.1					61.1			
175		29.8					29.8			
200										
225										
250										
275										
Total		469.9	37.9	524.4	173.6	71.3	1277.1			
Dead P			8.9					8.9		
				al Volumes						
17.5 +		469.9	37.9	524.4	173.6	71.3	1277.1	8.9		
22.5 +		469.9	37.9	524.4	173.6	71.3	1277.1	8.9		
27.5 +		469.9	37.9	524.4	165.4	71.3	1268.9	8.9		
32.5 +		469.9	37.9	524.4	147.0	71.3	1250.5	8.9		
37.5 +		469.9	37.9	524.4	147.0	71.3	1250.5	8.9		
42.5 +		469.9	37.9	480.9	105.9	60.2	1154.8	8.9		
47.5 +		469.9	19.7	445.7	88.1	46.2	1069.6	8.9		

^{*** 1} tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright0 1996-2013, Industrial Forestry Service Ltd.

Cutting Permit Basal Area Table (m2/ha)
Grades: Cruiser Called Alpha FIZ: B
Cruiser Est Decay PSYU: Quadra
Cruiser Est Waste Region: 2 - West Coast
CGNF Breakage Table District: 04 - South Island Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

CBASL- 1 , p18 04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

[A : 9.9]

		F	C	Н	В	YC	Total	DP	DU	LU
Utilization 1										
	n (M)	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
	n (M)	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0
	n (M)	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0
	n	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0
DBH										
Class										
5										
10										
15										
20										1.6
25					1.6		1.6			
30					2.1		2.1			
35 40				F 2	4 1	1.0	10.0			
45			2.1	5.3	4.1	1.6	10.9 9.0			
50			2.1	3.7	1.6	1.6				
55				1.6 6.8	1.6		3.1 6.8			
60				1.6		2.1	3.7			
65				3.1		2.1	3.1			
70		1.6		1.6	1.6		4.7			
75		1.0		3.1	1.0	2.1	5.3	2.1		
80				3.1		2.1	3.1	2.1		
85			1.6	3.1			1.6			
90		1.6	1.0	1.6			3.1			
95		2.1		3.1	1.6		6.8			
100		5.8		3.1	1.6		10.5			
105		5.3		3.1			8.4			
110		3.7		1.6			5.3			
115		3.1		1.6			4.7			
120		2.1					2.1			
125		3.6					3.6			
130										
135										
140		1.6					1.6			
145										
150		4.3					4.3			
175		2.1					2.1			
200										
225										
250										
275										
Total		36.9	3.7	43.8	15.6	7.4	107.4			
Dead P			2.1					2.1		
Dead U				1 6						1.6
Live U			7	1.6	7.mon /)	orrola			1.6
12.5 +		36.9		age Basal 43.8		7.4		2.1		1.6
17.5 +		36.9	3.7 3.7	43.8	15.6 15.6	7.4	107.4 107.4	2.1		1.6
22.5 +		36.9	3.7	43.8	15.6	7.4	107.4	2.1		1.6
27.5 +		36.9	3.7	43.8	14.0	7.4	107.4	2.1		
32.5 +		36.9	3.7	43.8	11.9	7.4	103.8	2.1		
J4.J T		20.5	3.1	43.0	11.7	/.4	103.7	∠.⊥		

^{*** 1} tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright0 1996-2013, Industrial Forestry Service Ltd.

*** FOR MPS PURPOSES *** BSTND- 1 , p19

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2 Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

Block Stand Table (stems/ha) ha FIZ: B PSYU: Quadra Region: 2 - West Coast District: 04 - South Island

04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Block : (N	M) -	001:CB	TS2,	Plots	s in Blo	ock: 12,	TUs: [A	A: 9.9]				
				F	C	Н	В	YC	Total	DP	DU	LU
Utilizatio												
Min DBH		(M)		.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
Stump Ht				. 0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0
Top Dia		(M)		. 0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0
Log Len	m		13	.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0
DBH Class												
5												
10												
15												
20												63.2
25							33.0		33.0			
30							35.1		35.1			
35												
40						42.5	31.9	13.3	87.7			
45					12.2	23.1	10.7	9.7	55.6			
50						8.6	7.7		16.3			
55						30.7			30.7			
60						5.4		7.2	12.6			
65 70				. 0		8.9 4.3	3.8		8.9 12.2			
75			4	. 0		7.3	3.8	5.0	12.2	4.9		
80						5.9		5.0	5.9	4.9		
85					2.6	3.5			2.6			
90			2	.6		2.3			4.9			
95				.1		4.4	2.2		9.6			
100			7	.6		4.0	2.1		13.8			
105				.1		3.5			9.6			
110				.9		1.6			5.5			
115				.1		1.4			4.6			
120				. 9					1.9			
125 130			2	.9					2.9			
135												
140			1	. 0					1.0			
145			_	. 0					1.0			
150			2	. 4					2.4			
175				.9					0.9			
200												
225												
250												
275												
Total			39	.5	14.8	154.0	126.4	35.2	369.8			
Dead P					4.9					4.9		
Dead U Live U						63.2						63.2
rive o					Δτε	erage DBH(cm) at 5	T.evrels				03.2
12.5 +			109	.1	56.5	60.2	39.6	51.8	60.8	75.0		17.7
17.5 +			109		56.5	60.2	39.6	51.8	60.8	75.0		17.7
22.5 +			109		56.5	60.2	39.6	51.8	60.8	75.0		
27.5 +			109		56.5	60.2	43.8	51.8	63.2	75.0		
32.5 +			109	.1	56.5	60.2	51.0	51.8	66.1	75.0		

*** FOR MPS PURPOSES *** BSTCK- 1 , p20

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

Block Stock Table (m3/ha) ta FIZ: B PSYU: Quadra Region: 2 - West Coast District: 04 - South Island

04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Block : (M)	- 001:CB	TS2, Plot	s in Blo	ck: 12,	TUs: [A	. : 9.9]				
		F	C	H	В	YC	Total	DP	DU	LU
Utilization	Limits									
Min DBH c	m (M)	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
Stump Ht c		30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0
	m (M)	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0
	m	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0
DBH										
Class										
5 10										
15										
20										
25					8.2		8.2			
30					18.4		18.4			
35					10.1		10.1			
40				43.5	41.1	11.1	95.7			
45			18.2	35.2	17.8	14.0	85.1			
50				11.6	17.6		29.2			
55				73.4			73.4			
60				17.7		23.2	40.9			
65				38.6			38.6			
70		17.1		17.2	22.6		57.0			
75				35.2		23.0	58.2	8.9		
80 85			19.7	40.6			40.6			
90		18.2	19.7	20.8			19.7 39.0			
95		22.4		53.0	25.8		101.2			
100		73.4		38.7	22.1		134.3			
105		53.5		55.1	22.1		108.6			
110		55.9		22.5			78.3			
115		40.2		21.2			61.5			
120		32.8					32.8			
125		42.4					42.4			
130										
135										
140		23.0					23.0			
145										
150		61.1					61.1			
175 200		29.8					29.8			
225										
250										
275										
Total		469.9	37.9	524.4	173.6	71.3	1277.1			
Dead P			8.9					8.9		
				al Volume	s for 7 I	evels				
17.5 +		469.9	37.9	524.4	173.6	71.3	1277.1	8.9		
22.5 +		469.9	37.9	524.4	173.6	71.3	1277.1	8.9		
27.5 +		469.9	37.9	524.4	165.4	71.3	1268.9	8.9		
32.5 +		469.9	37.9	524.4	147.0	71.3	1250.5	8.9		
37.5 +		469.9	37.9	524.4	147.0	71.3	1250.5	8.9		
42.5 +		469.9	37.9	480.9	105.9	60.2	1154.8	8.9		
47.5 +		469.9	19.7	445.7	88.1	46.2	1069.6	8.9		

*** FOR MPS PURPOSES *** BBASL- 1 , p21

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Block : ((M) -	001:CB	TS2,	Plots	in Blo	ock: 12,	TUs: [A : 9.9	1			
				F	С	Н	В	YC	Total	DP	DU	LU
Utilizati Min DBH Stump Ht Top Dia Log Len DBH	cm cm	(M) (M) (M)	17 30 15 13	.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	30.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0
Class 5 10 15												
20 25 30 35							1.6 2.1		1.6 2.1			1.6
40 45					2.1	5.3 3.7	4.1 1.6	1.6 1.6	10.9 9.0			
50 55 60						1.6 6.8 1.6	1.6	2.1	3.1 6.8 3.7			
65 70 75			1	.6		3.1 1.6 3.1	1.6	2.1		2.1		
80 85 90			1	.6	1.6	3.1 1.6			3.1 1.6 3.1			
95 100 105			2 5	.1 .8 .3		3.1 3.1 3.1	1.6 1.6		6.8 10.5 8.4			
110 115 120			3 2	.7 .1 .1		1.6 1.6			5.3 4.7 2.1			
125 130 135			3	.6					3.6			
140 145				.6					1.6			
150 175 200 225 250				.3					4.3 2.1			
275 Total Dead P			36	.9	3.7 2.1	43.8	15.6	7.4	107.4	2.1		
Dead U Live U					7	1.6	al Amos (m2) a+ F	T orrol a			1.6
12.5 + 17.5 + 22.5 +			36 36 36	.9	3.7 3.7 3.7	43.8 43.8 43.8 43.8	15.6 15.6 15.6 15.6	m2) at 5 7.4 7.4 7.4	107.4 107.4	2.1 2.1 2.1		1.6 1.6
27.5 + 32.5 +			36 36		3.7 3.7	43.8 43.8	14.0 11.9	7.4 7.4	105.8	2.1 2.1		

^{*** 1} tree(s) changed to tree class 6:because only log was less then 3.00 m ***
FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage,
CruiseComp Copyright® 1996-2013, Industrial Forestry Service Ltd.

*** FOR MPS PURPOSES *** TSTND- 1 , p22 04-Nov-2015 02:42:44PM

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

Type Stand Table (stems/ha) ha FIZ: B PSYU: Quadra Region: 2 - West Coast District: 04 - South Island

04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Type 1 (M):FdHw (BaCy), Plots in Type: 1, TUs: [A : 0.5]

Abe I (N	1):FdHw (Ba	icy), Piots	in Type	: I, TUS:	[A : 0.5]				
		F	C	Н	В	YC	Total	DP	DU	L
tilizatio		17 5	17 5	17 5	17 5	17 5	17 5	17 5	17 5	17.
Min DBH Stump Ht	cm (M)	17.5 30.0	30.							
Top Dia	cm (M)	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.
Log Len	m (M)	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.
DBH	ш	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13
lass										
5										
10										
15										
20										
25										
30										
35										
40					160.0		160.0			
45										
50										
55										
60										
65										
70										
75										
80										
85										
90 95										
100										
105										
110										
115										
120										
125		33.1					33.1			
130		33.1					33.1			
135										
140										
145										
150										
175										
200										
225										
250										
275										
otal		33.1			160.0		193.1			
ead P										
ead U										
ive U										
			Ave	rage DBH(c		evels				
2.5 +		124.0			39.9		62.9			
7.5 +		124.0			39.9		62.9			
2.5 +		124.0			39.9		62.9			
7.5 +		124.0			39.9		62.9			
2.5 +		124.0			39.9		62.9			

TSTND- 2 , p23

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

Type Stand Table (stems/ha) ha FIZ: B PSYU: Quadra Region: 2 - West Coast District: 04 - South Island

04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Time	2	(M):FdHw(CyCwBa),	Dlote	in	Tyme:	2	TITe:	Γ :	Δ		1 7	
Type .	4	(M) · runw(Cycwba),	PIULS	TII	TAbe.	Ζ,	108.		M	•	1./	

1700 2	(II) I allw (Cyc	wba,, riot	b in type	2, 105	. [A . 1	. , ,				
		F	С	Н	В	YC	Total	DP	DU	LU
Utilizat	ion Limits									
Min DBH		17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
	t cm (M)	30.0	30.0	30.0	30.0	30.0	30.0		30.0	30.0
Top Dia		15.0 13.0	15.0 13.0	15.0 13.0	15.0 13.0	15.0 13.0	15.0 13.0	15.0 13.0	15.0 13.0	15. 13.
Log Len DBH	m	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.
Class										
5										
10										
15										
20										
25 30					204.5		204.5			
35					204.5		204.5			
40				95.1			95.1			
45			70.8	75.5			146.4			
50										
55				54.4			54.4			
60						41.9	41.9			
65 70										
75						29.4	29.4	28.3		
80						27.1	27.1	20.5		
85										
90										
95		17.8					17.8			
100 105		32.4 14.2					32.4 14.2			
110		12.9					12.9			
115		12.7					12.7			
120		10.9					10.9			
125										
130										
135 140										
145										
150		13.7					13.7			
175		5.3					5.3			
200										
225										
250										
275 Fotal		107.2	70.8	225.1	204.5	71.3	678.9			
Dead P		107.2	28.3	225.1	204.5	/1.3	6/8.9	28.3		
Dead U			20.5					20.5		
Live U										
					cm) at 5 1					
12.5 +		115.6	47.4	46.1	27.9			75.0		
17.5 + 22.5 +		115.6 115.6	47.4		27.9 27.9	66.8 66.8	61.2 61.2	75.0 75.0		
22.5 + 27.5 +		115.6	47.4	46.1 46.1		66.8	61.2	75.0		
32.5 +		115.6	47.4	46.1	27.5	66.8	70.9	75.0		

TSTND- 3 , p24 04-Nov-2015 02:42:44PM

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

Type Stand Table (stems/ha) ha FIZ: B PSYU: Quadra Region: 2 - West Coast District: 04 - South Island

04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Type 3	<pre>(M):HwFd(BaCvCw).</pre>	Plots in	Type: 9	. TUs:	[A : 7.7

		F	C	Н	В	YC	Total	DP	DU	LU
Utilizatio										
Min DBH	cm (M)	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
Stump Ht Top Dia	cm (M)	30.0 15.0	30.0 15.0	30.0 15.0	30.0 15.0	30.0 15.0	30.0 15.0	30.0 15.0	30.0 15.0	30.0 15.0
Log Len	m (M)	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0
DBH	111	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0
Class										
5										
10										
15 20										81.
25					42.4		42.4			81.
30					12.1		12.1			
35										
40				33.7	30.6	17.1	81.3			
45				13.0	13.7	12.4	39.2			
50 55				11.1 27.4	9.9		20.9			
60				6.9			27.4 6.9			
65				11.4			11.4			
70		5.2		5.6	4.9		15.7			
75				9.4			9.4			
80				7.6			7.6			
85 90		3.3	3.4	3.0			3.4			
95		3.3		5.6	2.8		6.3 8.4			
100		2.7		5.2	2.7		10.6			
105		4.7		4.5			9.2			
110		2.2		2.1			4.3			
115		4.0		1.9			5.9			
120										
125 130		1.6					1.6			
135										
140		1.3					1.3			
145										
150										
175										
200 225										
250										
275										
rotal		25.0	3.4	148.3	107.0	29.5	313.1			
Dead P										
Dead U										0.0
Live U			7 tro	81.3	cm) at 5 1	l erre l c				81.
12.5 +		101.0	87.0				60.5			17.
17.5 +		101.0	87.0			41.6	60.5			17.
00 =		101.0		64.2		41.6	60.5			
						41 (
22.5 + 27.5 + 32.5 +		101.0 101.0	87.0 87.0	64.2 64.2	52.5 52.5	41.6	64.3 64.3			

*** FOR MPS PURPOSES *** TSTCK- 1 , p25 Type Stock Table (m3/ha)
FIZ: B
PSYU: Quadra
Region: 2 - West Coast
District: 04 - South Island 04-Nov-2015 02:42:44PM Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Type 1 (M):FdHw (BaCy), Plots in Type: 1, TUs: [A : 0.5]

Type I (M)	FOHW (Ba	Cy), Piots	in Type	: I, TUS:	[A : U.5	1				
		F	C	Н	В	YC	Total	DP	DU	LU
Jtilization										
	cm (M)	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.
Stump Ht		30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.
	cm (M)	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.
Log Len	m	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.
DBH										
Class 5										
10										
15										
20										
25										
30										
35										
40					207.7		207.7			
45										
50										
55										
60										
65										
70										
75										
80										
85										
90										
95										
100										
105										
110 115										
120										
125		395.6					395.6			
130		393.0					393.0			
135										
140										
145										
150										
175										
200										
225										
250										
275										
Total		395.6			207.7		603.3			
Dead P										
			Tota	al Volumes	for 7 Le	vels				
17.5 +		395.6			207.7		603.3			
22.5 +		395.6			207.7		603.3			
27.5 +		395.6			207.7		603.3			
32.5 +		395.6			207.7		603.3			
37.5 +		395.6			207.7		603.3			
42.5 +		395.6					395.6			
47.5 +		395.6					395.6			

TSTCK- 2 , p26

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

Type Stock Table (m3/ha)
FIZ: B
PSYU: Quadra
Region: 2 - West Coast
District: 04 - South Island

04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Type 2	(M):FdHw(CyCwBa),	Plots	in	Type:	2.	TUs:	Γ	Α	:	1.7	

1700 2 (1	i) · I dliw (C) (cwba,, iio	CD III IYP	C. 2, 105						
		F	C	Н	В	YC	Total	DP	DU	L
Utilizatio	n Limits									
Min DBH	cm (M)	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.
Stump Ht		30.0			30.0	30.0	30.0	30.0	30.0	30.
Top Dia		15.0	15.0		15.0	15.0	15.0	15.0	15.0	15.
	m	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.
DBH Class										
5										
10										
15										
20										
25										
30					106.9		106.9			
35										
40				100.1			100.1			
45			105.9	117.8			223.7			
50 55				145.4			145.4			
60				143.4		135.2	135.2			
65						133.2	133.2			
70										
75						133.8	133.8	51.6		
80										
85										
90										
95		130.3					130.3			
100 105		303.0 119.5					303.0 119.5			
110		189.7					189.7			
115		105.7					105.7			
120		191.0					191.0			
125										
130										
135										
140										
145										
150		355.9					355.9			
175 200		173.8					173.8			
225										
250										
275										
rotal		1463.1	105.9	363.4	106.9	269.0	2308.2			
Dead P			51.6					51.6		
				al Volume	s for 7 I	Levels				
L7.5 +		1463.1	105.9	363.4	106.9		2308.2	51.6		
22.5 +		1463.1		363.4	106.9		2308.2	51.6		
27.5 +		1463.1		363.4	106.9	269.0	2308.2	51.6		
32.5 + 37.5 +		1463.1 1463.1	105.9	363.4 363.4		269.0 269.0	2201.3 2201.3	51.6 51.6		
12.5 +		1463.1	105.9 105.9	263.3		269.0	2101.3	51.6		
47.5 +		1463.1	103.9	145.4		269.0	1877.5	51.6		
17.5		1100.1		113.1		200.0	10//.5	31.0		

*** FOR MPS PURPOSES *** Average Line Method ALBERNI VALLEY COM FOREST

Type Stock Table (m3/ha)
FIZ: B
PSYU: Quadra Grades: Cruiser Called Alpha Cruiser Est Decay Region: 2 - West Coast District: 04 - South Island Cruiser Est Waste

Licence Number: 000 CP: 00 CGNF Breakage Table

Type 3 (M):HwFd(BaCyCw), Plots in Type: 9, TUs: [A : 7.7] В DU F C H YC Total DP LU Utilization Limits Min DBH cm (M)
Stump Ht cm (M)
Top Dia cm (M)
Log Len m
DBH 17.5 17.5 17.5 17.5 17.5 17.5 17.5 17.5 17.5 30.0 15.0 30.0 30.0 30.0 30.0 15.0 30.0 15.0 30.0 30.0 30.0 15.0 13.0 13.0 13.0 13.0 13.0 13.0 13.0 13.0 13.0 Class 5 10 15 20 25 30 35 40 45 50 55 60 10.5 10.5 33.9 19.2 15.0 62.3 39.4 22.9 22.6 14.3 18.0 60.1 37.6 62.3 22.8 22.8 49.6 22.1 65 70 75 80 85 90 95 49.6 22.0 29.1 73.3 45.3 52.2 25.4 45.3 25.4 23.3 26.8 68.1 50.1 33.2 101.4 27.5 42.4 29.9 51.7 49.8 70.8 28.9 100 105 105.7 113.2 28.4 110 115 120 58.8 27.3 79.0 125 130 28.8 28.8 135 140 29.5 145 150 175 200 225 250 275 255.4 25.4 594.0 186.1 32.3 1093.1 Total Dead P Volumes for Total 17.5 + 22.5 + 27.5 + 32.5 + 42.5 + 25.4 25.4 25.4 25.4 25.4 25.4 32.3 32.3 32.3 594.0 594.0 594.0 255.4 186.1 1093.1 255.4 255.4 255.4 255.4 255.4 255.4 186.1 186.1 175.6 175.6 175.6 136.2 1093.1 1082.6

*** 1 tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright@ 1996-2013, Industrial Forestry Service Ltd.

594.0 594.0

560.1

32.3

18.0

1082.6 1082.6

995.1

TSTCK- 3 , p27

04-Nov-2015 02:42:44PM 04-NOV-2015 02-42-44FM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

TBASL- 1 , p28

Type Basal Area Table (m2/ha)

Grades: Cruiser Called Alpha FIZ: B
Cruiser Est Decay PSYU: Quadra
Cruiser Est Waste Region: 2 - West Coast
CGNF Breakage Table District: 04 - South Island

04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Time 1	(M):FdHw	(BaCtr)	Dlote	in	Time:	1	TITe:	Γ	Δ		0.5	
Type T	(M) · ranw	(Dacy),	PIULS	TII	Type.	Ι,	108.	L	м	•	0.5	

Type I (M	i).runw (ba	Cy), FIOLE	III IYPE	. 1, 105.	[A . U.J	,				
		F	C	Н	В	YC	Total	DP	DU	LU
Jtilizatio										
Min DBH	cm (M)	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
Stump Ht		30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.
Top Dia	cm (M)	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.
Log Len	m	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.
DBH lass										
5										
10										
15										
20										
25										
30										
35										
40					20.0		20.0			
45										
50										
55										
60 65										
70										
75										
80										
85										
90										
95										
100										
105										
110										
115										
120 125		40.0					40.0			
130		40.0					40.0			
135										
140										
145										
150										
175										
200										
225										
250										
275										
Total		40.0			20.0		60.0			
Dead P Dead U										
Live U										
TTAE O			Ave	rage Basal	Area (m2) at 5 T	evels			
12.5 +		40.0	11703	- Dabas	20.0	, ac 5 1	60.0			
17.5 +		40.0			20.0		60.0			
22.5 +		40.0			20.0		60.0			
27.5 +		40.0			20.0		60.0			
32.5 +		40.0			20.0		60.0			

Type Basal Area Table (m2/ha)

Grades: Cruiser Called Alpha FIZ: B
Cruiser Est Decay PSYU: Quadra
Cruiser Est Waste Region: 2 - West Coast
CGNF Breakage Table District: 04 - South Island Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

TBASL- 2 , p29 04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Type 2 (M):FdHw(CyCwBa), Plots in Type: 2, TUs: [A : 1.7]

Type 2 (M):FdHw(CyC	wBa), Plot	s in Type	e: 2, TUs:	[A : 1	.7]				
		F	C	Н	В	YC	Total	DP	DU	LU
	on Limits									
Min DBH	cm (M)	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
	cm (M)	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0
Top Dia Log Len	cm (M)	15.0 13.0	15.0 13.0	15.0 13.0	15.0 13.0	15.0 13.0	15.0 13.0	15.0	15.0 13.0	15.0 13.0
DBH	m	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0	13.0
lass										
5										
10										
15										
20										
25										
30					12.5		12.5			
35										
40				12.5			12.5			
45			12.5	12.5			25.0			
50 55				12.5			12.5			
60				12.5		12.5	12.5			
65						12.5	12.5			
70										
75						12.5	12.5	12.5		
80										
85										
90										
95		12.5					12.5			
100		25.0					25.0			
105		12.5					12.5			
110		12.5					12.5			
115		10 5					10 5			
120 125		12.5					12.5			
130										
135										
140										
145										
150		25.0					25.0			
175		12.5					12.5			
200										
225										
250										
275										
otal		112.5	12.5	37.5	12.5	25.0	200.0			
ead P			12.5					12.5		
ead U										
ive U			Δικον	age Basal	Area /m'	2) at 5 T	evel e			
2.5 +		112.5	12.5	37.5	12.5	25.0	200.0	12.5		
7.5 +		112.5	12.5	37.5	12.5	25.0	200.0	12.5		
2.5 +		112.5	12.5	37.5	12.5	25.0	200.0	12.5		
7.5 +		112.5	12.5	37.5	12.5	25.0	200.0	12.5		
32.5 +		112.5	12.5	37.5		25.0	187.5	12.5		

TBASL- 3 , p30 Type Basal Area Table (m2/ha)

Grades: Cruiser Called Alpha FIZ: B
Cruiser Est Decay PSYU: Quadra
Cruiser Est Waste Region: 2 - West Coast
CGNF Breakage Table District: 04 - South Island 04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

Type 3	(M):HwFd(BaCyCw),	Plots in	Type: 9	TUs:	[A :	7.7

Type 3	(M):HwFd(BaCy	Cw), Plot	s in Type	e: 9, TUs:	[A : 7	.7]				
		F	С	Н	В	YC	Total	DP	DU	LU
Min DBH	t cm (M) cm (M)	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0	17.5 30.0 15.0 13.0
Class 5 10 15										
20 25 30 35					2.0		2.0			2.0
40 45				4.0	4.0	2.0	10.0 6.0			
50 55 60				2.0 6.0 2.0	2.0		4.0 6.0 2.0			
65 70 75		2.0		4.0 2.0 4.0	2.0		4.0 6.0 4.0			
80 85 90		2.0	2.0	4.0			4.0 2.0 4.0			
95 100 105		2.0		4.0 4.0 4.0	2.0		6.0 8.0 8.0			
110 115 120		2.0 4.0		2.0			4.0 6.0			
125 130 135		2.0					2.0			
140 145 150		2.0					2.0			
175 200 225										
250 275 Total Dead P		20.0	2.0	48.0	16.0	4.0	90.0			
Dead U Live U				2.0		· · · · · · · · ·				2.0
12.5 + 17.5 + 22.5 +		20.0 20.0 20.0	2.0 2.0 2.0	age Basal 48.0 48.0 48.0	16.0 16.0 16.0	4.0 4.0 4.0 4.0	90.0 90.0 90.0			2.0
27.5 + 32.5 +		20.0	2.0	48.0 48.0	14.0 14.0	4.0	88.0 88.0			

*** FOR MPS PURPOSES *** PLSUM- 1 , p31 Plot Summary

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2 Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

FIZ: B PSYU: Quadra Region: 2 - West Coast District: 04 - South Island 04-Nov-2015 02:42:44PM 04-NOV-2015 02-42.44FM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Utilization Levels: Minimum DBH Top Diameter Stump Height Mature Blocks: (cm) 17.5 15.0 Immature Blocks:(cm)

Standard Log Length:(m) 13.00

Cruise Forest Plot Slope # of Stems Ava Gross Less Less Less Loss Ref No. Species Stems YI OI M Type / Ha Diam Merch Decay Date 238.16 427.50 665.66 39.90 124.00 220.83 417.77 1-FdHw (BaCy) 001 2 20.000F 90 Balsam 159.95 207 71 207.71 Doug-Fir 33.12 395.64 395.64 638.60 All Sp. 3 193.08 62.90 603.35 603.35 1511 W.R. Cedar 001 2 3 25.000F 108 56.59 75.00 167.43 133.24 121.50 103.13 2-FdHw(CyCwBa) 1 56.59 146.40 75.00 123.37 167.43 2596.26 133.24 2532.10 121.50 2397.69 E-Down 103.13 2386.79 Doug-Fir Hemlock 299 04 46.14 549 13 521 64 491 10 491 10 All Sp. 79.63 3312.82 502.03 3186.98 3010.28 27.90 47.40 96.77 227.45 240.48 569.59 4 25.000F 408.92 248.23 Balsam W.R. Cedar Doug-Fir 224.44 539.41 141.68 67.98 245.81 211.73 539.41 2 582 85 Hemlock 265.31 607.09 250.44 578.53 Y. Cedar 142.65 66.80 537.93 537.93 All Sp. 912.31 49.42 1949.28 1866.49 1751.23 1738.52 1511 W.R. Cedar Doug-Fir 30.28 112.17 87.00 90.40 245.85 1067.90 244.47 1043.60 228.42 988.31 228.42 922.22 3-HwFd(BaCyCw) 001 2 5 18.000F 108 Hemlock 132.89 71.93 867.50 824.08 775.82 775.82 All Sp. 2181.25 1992.56 1511 6 18.000F 64 Doug-Fir 3 51.99 115.00 829.01 810.14 767.22 767 22 105.70 370.50 Hemlock 20.51 392.05 348.69 348.69 All Sp. 4 72.51 112.44 1221.06 1180.64 1115.91 1115.91 1511 2 8 18.000F Balsam 525.77 349.75 326.62 307.35 307.35 113 29.53 Hemlock All Sp. 16.66 542.43 117.30 35.60 274.71 624.46 260.95 587.57 245.67 553.01 553.01 1511 9 18.000F Balsam Doug-Fir Hemlock 18.11 149.99 112.50 78.18 240.38 973.23 1 253.06 227.28 915.63 227.28 1035.26 1511 All Sp. 6 193.23 84.36 1630.94 1531.57 1442.00 1424.19 2 10 18.000F 78 Hemlock 886.87 809.01 All Sp. 80.44 92.45 886.87 809.01 759.67 741.15 1511 2 11 18.000F Doug-Fir 42.30 104.10 412.61 403.22 381.86 42.74 41.55 743.09 313.02 Hemlock 4 501.81 785.90 697 61 697 61 Cedar Y. Cedar All Sp. 47.59 1511 8 809.61 1532.68 1459.32 1370.13 1370.13 865.65 2 12 18.000F 40 Hemlock 163.24 919.67 865.10 All Sp. 163.24 74.94 971.11 919.67 865.65 865.10 1511 71.80 297.97 278.26 261.84 261.84 2 13 18.000F 55 Balsam 44.46 Hemlock 1511 All Sp. 5 313.66 60.44 1201.71 1102.59 1035.90 1035.90 2 14 18.000F 95 Balsam 367.46 49.95 952.93 868.04 815.53 806.42 17.70 32.29 Hemlock 731 54

1099.00

952.93 868.04 815.53 806.42

FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright@ 1996-2013, Industrial Forestry Service Ltd.

All Sp.

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

Plot Frequency Report
FIZ: B
PSYU: Quadra
Region: 2 - West Coast
District: 04 - South Island

PLFRQ- 1 , p32 04-Nov-2015 02:42:44PM
Filename: cbts2_2015opc_20151104.ccp
Compiled by: Contour Forest Consultants Inc
Cruised by: CONTOUR FOREST CONSULTANTS INC
Version: 2014.00 IFS build 5888

Measure Plots

Measure FIGUS			
Blocks	Timber	Type	
	1	2	3
BLOCK 001 (M) # of Plots ha / Plot	10.50	2 0.85	9 0.86
Cutting Permit # of Plots ha / Plot	1 0.50	2 0.85	9 0.86

FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright© 1996-2013, Industrial Forestry Service Ltd.

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

Plot Frequency Report
FIZ: B
PSYU: Quadra
Region: 2 - West Coast
District: 04 - South Island

PLFRQ- 2 , p33 04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Measure Plots			
Harvest Methods	Timber 1	Type 2	3
METHOD CC # of Plots ha / Plot		0.40	
METHOD HL # of Plots ha / Plot		1.30	0.50
METHOD SC # of Plots ha / Plot	1 0.50		8 0.90
All Methods # of Plots ha / Plot	1 0.50	2 0.85	9 0.86

FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyrights 1996-2013, Industrial Forestry Service Ltd.

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

Plot Frequency Report
FIZ: B
PSYU: Quadra
Region: 2 - West Coast
District: 04 - South Island

PLFRQ- 3 , p34 04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Count Plots Blocks Timber Type

BLOCK 001 (M) # of Plots ha / Plot

Cutting Permit # of Plots ha / Plot

FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright© 1996-2013, Industrial Forestry Service Ltd.

Average Line Method ALBERNI VALLEY COM FOREST Licence Number: 000 CP: 00 Project: TS2

Grades: Cruiser Called Alpha Cruiser Est Decay Cruiser Est Waste CGNF Breakage Table

Plot Frequency Report
FIZ: B
PSYU: Quadra
Region: 2 - West Coast
District: 04 - South Island

PLFRQ- 4 , p35 04-Nov-2015 02:42:44PM 04-Nov-2015 02:42:44PM Filename: cbts2_2015opc_20151104.ccp Compiled by: Contour Forest Consultants Inc Cruised by: CONTOUR FOREST CONSULTANTS INC Version: 2014.00 IFS build 5888

Count Plots

Harvest Methods	Timber 1	Type 2	3
METHOD CC # of Plots ha / Plot			
METHOD HL # of Plots ha / Plot			
Marrian ag			

METHOD SC # of Plots ha / Plot

All Methods # of Plots ha / Plot

FLAGS: Full Volumes, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright© 1996-2013, Industrial Forestry Service Ltd.



COMMUNITY FOREST AGREEMENT K2D CUTTING PERMIT NO. 009

Ministry of Forests, Lands and Natural Resource Operations

PURSUANT TO the Community Forest Agreement No. **K2D** (the "Agreement"), this Cutting Permit is issued to:

ALBERNI VALLEY COMMUNITY FOREST CORPORATION

7500 Airport Road
Port Alberni, British Columbia
V9Y 8Y9
(the "Agreement Holder")

1.00 PERMIT AREA AND TERM

- 1.01 Subject to the Agreement and the Forestry Legislation, the Agreement Holder is authorized to cut and Remove timber from the areas of lands within the Agreement Area that are designated on the map attached as Exhibit "A" to this Cutting Permit.
- 1.02 Subject to the Agreement, the term of this Cutting Permit is **4** years, beginning on the date signed by the District Manager (See Page 3).

2.00 SPECIAL CONDITIONS AND REQUIREMENTS

2.01 The Agreement Holder must comply with the conditions and requirements set out in Schedule "A" to this Cutting Permit.

3.00 TIMBER REMOVED AND WASTE ASSESSMENT

3.01 The timber described in Schedule "B" is specified as reserved timber and the Agreement Holder must not fell standing timber, and must not buck or Remove felled or dead and down timber, as the case may be, of the species and description set out in Schedule "B".

4.00 TIMBER MARKS

4.01 The timber mark(s) for timber Removed from land identified as Schedule B Land in the Agreement under this Cutting Permit is/are:

K2D 009

- 4.02 The timber mark for timber Removed from land identified as Schedule A Land in the Agreement under this Cutting Permit is/are: **Not Applicable**
- 4.03 If directed to do so by the District Manager, the Agreement Holder must erect signs at all exits from the areas of land referred to in paragraph 1.01, clearly showing the timber mark(s) referred to in paragraphs 4.01 and 4.02.

5.00 SCALE-BASED STUMPAGE

- 5.01 The Agreement Holder must ensure that
 - (a) all timber Removed from the areas of land referred to in paragraph 1.01 is scaled, and
 - (b) the scale of the timber is conducted properly in accordance with the requirements of the *Forest Act* and the regulations made under that Act.
- 5.02 For the purpose of determining the amount of stumpage payable in respect of timber Removed from the areas of Schedule B Land in the Agreement, authorized for cutting and Removal under this Cutting Permit, the volume or quantity of timber Removed will be determined using information provided in a scale of the timber.

6.00 ROADS

Subject to the Agreement and the Forestry Legislation, the Agreement Holder may use, construct, modify, maintain or deactivate roads on the area covered by this Cutting Permit.

7.00 HARVESTING OPERATIONS

- **7.01** The Agreement Holder must ensure that
 - (a) all phases of timber cutting and Removal and related operations under or associated with this Cutting Permit are synchronized, and

- (b) all operations on one area designated for cutting and Removal of timber under this Cutting Permit is completed to the satisfaction of the District Manager before operations are commenced on another area.
- **7.02** The Agreement Holder must not erect or operate a sawmill or wood processing plant on an area of land referred to in paragraph 1.01 of this Cutting Permit.
- **7.03** The rights granted under this Cutting Permit are subject to other rights of use and occupation, and the Agreement Holder must not interfere with the exercise of those rights.
- **7.04** The Agreement Holder must not allow the manufacture of special forest products on the area of land described in paragraph 1.01 of this Cutting Permit, unless authorized to do so by the District Manager.

MISCELLANEOUS

- 8.01 The Schedules and Exhibit "A" to this Cutting Permit are deemed to be part of this Cutting Permit.
- 8.02 As provided in the Agreement, this Cutting Permit is deemed to be part of the Agreement.
- 8.03 The Agreement governs the interpretation of this Cutting Permit.

K2D CP009 - Version 1.05.doc March 19, 2014

SCHEDULE "A" SPECIAL CONDITIONS AND REQUIREMENTS

1.00 TIMING OF OPERATIONS

The Licensee must ensure that all phases of timber harvesting and related operations under or associated with this Cutting Permit are synchronized.

2.00 ORDERLY CONDITION

The Licensee shall, concurrently with harvesting operations, leave all areas in an orderly and sanitary condition.

3.00 DANGEROUS TREES

- 3.01 The Licensee may fell trees outside of the cutblock boundary(s) identified on the attached map as Exhibit "A", for the purposes of tree felling to eliminate a safety hazard, if the person conducting tree felling or rigging tail hold/anchor trees determines that the tree is a dangerous tree according to Work Safe BC regulations and it is within 50 metres beyond the cutting authority area.
- 3.02 No authorization is given to fell, damage, alter or utilize timber located outside of the boundaries of Crown land associated with Community Forest Licence K2D.

4.00 TIMBER MARKS

- 4.01 In reference to paragraph 4.03 of the Cutting Permit, the Licensee must erect timber mark signs at all exits from the area of land or at changes of timber marks within the area of land referred to in the Cutting Permit paragraph 1.01, clearly showing the appropriate timber marks.
- 4.02 Harvesting operations must be conducted in a manner ensuring the accurate application of timber marks to timber to the satisfaction of the District Manager.

5.00 OTHER OCCUPIERS OF LAND

The rights granted under this Permit are subject to other rights of use and occupation and the Licensee must not interfere with exercise of those rights.

SCHEDULE "B"

1.00 RESERVED TIMBER

1.01 The following timber is specified as reserved timber:

Description (size, etc.)
All sizes and grades of timber, whether fallen or standing, dead or alive, within areas shown as "Timber Leave Area" on the 1:5000 scale "Cutting Permit Map" attached to this Cutting Permit are reserved from felling.
All sizes and grades of timber, whether fallen or standing, dead or live, within areas shown as 3.9% "Dispersed Retention" on the 1:5000 application 'Cutting Permit Map' for cutblock TS2 attached to this Cutting Permit are reserved timber except in the following circumstances: (a) If the person conducting tree felling or rigging tailhold/anchor trees determines that a tree represents a safety hazard according to Work Safe BC standards. Unless otherwise reserved from removal or harvesting in the applicable forest stewardship plan, any felled safety hazard trees may be removed. (b) Cutblock TS2 has been designed as a combination of small clearcut's and one polygon with a "Retention" silviculture system which consists of 3.9% of the timber being retained within eight small groups of leave trees. These groups of three to eight trees are uniformely dispersed within the harvest area as detailed in the attached tables titled "Leave Tree Report."





EXHIBIT A




MAP OF: K2D CP 009 (shown in bold black)						
FOREST REGION : RWC FOREST DISTRICT : DSI	TSA : 38 LAND DISTRICT : CLAYOQUOT DISTRICT		MGT UNIT TYPE : COMMUNITY FOREST MGT UNIT NO :			
ESF SUBMISSION ID : 1467846 BCGS MAPSHEET NO : 92F.024	SCALE : 1:20000 at A Size Area (Ha): 13.537		DRAWN BY : FTA DATE : Dec 9, 2015			









ALBERNI VALLEY COM FOREST

K2D - CP# PRE

Mount Taylor Block #: TS2

SUMMARY OF VOLUMES (loss factors)
LEAVE TREE REPORT

03-May-2016 11:34:03AM

Cruised by: CONTOUR FOREST CONSULTANTS INC

Compiled by: F Warren and Associates Ltd



LEAVE TREE REPORT

Block Summary

FIZ: B PSYU: Nootka

Region: 2 - West Coast District: 04 - South Island

Cruised by: CONTOUR FOREST CONSULTANTS IN

Compiled by: F Warren and Associates Ltd

03-May-2016 11:34:03AM Filename: TS2.ccp

BS- 1 , p2

Version: 2015.00 IFS build 5947

Average Line Method Grades: MOF Computerized ALBERNI VALLEY COM FOREST Computerized Decay Licence Number: K2D CP: PRE Computerized Waste Project: TS2 Computerized Breakage

Net Area: Block: (M) - 001:TS2, Plots in Block: 12, TUs: [All Treatment Units: 10.0]

		m - + - 1	G ! F	D		~	**		7.7
Utilization Limits		Total	Conifer	Decid	F	С	Н	В	Y
Min DBH cm (M)					17.5	17.5	17.5	17.5	17.5
Stump Ht cm (M)					30.0	30.0	30.0	30.0	30.0
Top Dia cm (M)					15.0	15.0	15.0	15.0	15.0
Log Len m					10.0	10.0	10.0	10.0	10.0
Volume and Size Data					10.0	10.0	10.0	10.0	10.0
Gross Merchantable	m3	378	378		179	8	178	10	3
Net Merchantable	m3	336	336		167	5	153	9	2
Net Merch - All	m3/ha	34	34		17	1	15	í	0
Distribution	%	100	100		50	2	46	3	1
Decay	%	5	5		2	18	7	5	11
Waste	%	1	1		0	9	2	1	0
Waste(billing)	%	1	1		0	14	2	1	0
Breakage	%	6	6		5	7	6	5	7
Total Cull (DWB)	%	11	11		7	35	14	11	18
Stems/Ha (Live & DP)	Ü	4.5	4.5		1.3	0.1	2.8	0.2	0.2
Avg DBH (Live & DP)	cm	83.0	83.0		104.7	87.0	74.0	64.2	45.3
Snags/Ha	J	03.0	05.0		1011,	0,10	, 1.0	01.2	10.0
Avg Snag DBH	cm								
Gross Merch Vol/Tree	m3	8.32	8.32		13.71	7.69	6.47	5.13	1.58
Net Merch Vol/Tree	m3	7.39	7.39		12.75	5.03	5.55	4.55	1.29
Avg Weight Total Ht	m	50.9	50.9		58.9	46.3	44.3	40.4	26.1
Avg Weight Merch Ht	m	44.9	44.9		53.4	39.0	37.2	34.9	19.7
Avg 10.0 m Log Net	m3	2.08	2.08		2.53	1.39	1.86	1.34	0.70
Avg 10.0 m Log Gross	m3	2.20	2.20		2.59	1.92	2.03	1.42	0.79
Avg # of 10.0 m Logs		3.78	3.78		5.30	4.00	3.19	3.60	2.00
Net Immature	%								
Net 2nd Growth	%								
Average Slope	%	77							
Algorithm Grades %									
#1 Lum/#1 Prem	D	16	16		30		4		
#2 Lum/#1 Lum	F								
#2 Sawlog	Н	21	21		13	50	29	36	
#3 Sawlog	I	42	42		44	19	38	37	
#4 Sawlog	J	4	4				8	7	
#4 Shingle	M					9			
#5 Utility	U	12	12		8	22	16	20	
#6 Utility	X	1	1				2		100
#7 Chipper	Y	4	4		5		3		
Statistical Summary									
Coeff. of Variation	용	112.0	112.0		229.2	346.4	81.8	277.8	346.4
Two Standard Error	%	73.1	73.1		149.7	226.2	53.4	181.4	226.2
Number and Type of P			12						
Number of Potential	Trees	65							
Plots/Ha		1.2							
Cruised Trees/Plot		5.5							
Slope % Statistics									

Min= 40, Max=113, CV=32.9, Std Error of Mean=7.3, 2SE%=20.9

*** 1 tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Leave Tree Report, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright© 1996-2015, Industrial Forestry Service Ltd.

Average Line Method

Project: TS2

ALBERNI VALLEY COM FOREST

Licence Number: K2D CP: PRE

LEAVE TREE REPORT

Block Summary

FIZ: B

Region: 2 - West Coast

District: 04 - South Island

Filename: TS2.ccp PSYU: Nootka

Compiled by: F Warren and Associates Ltd Cruised by: CONTOUR FOREST CONSULTANTS IN

BS- 2 , p3

Version: 2015.00 IFS build 5947

03-May-2016 11:34:03AM

Net Area: Block: (M) - 001:TS2, Plots in Block: 12, TUs: [A Block: 9.9]

		Total	Conifer	Decid	F	C	Н	В	Y
Utilization Limits		IUCAI	COULTE	Decia	F		- 11		1
Min DBH cm (M)					17.5	17.5	17.5	17.5	17.5
Stump Ht cm (M)					30.0	30.0	30.0	30.0	30.0
Top Dia cm (M)					15.0	15.0	15.0	15.0	15.0
Log Len m					10.0	10.0	10.0	10.0	10.0
olume and Size Data									
Gross Merchantable	m3	378	378		179	8	178	10	3
Net Merchantable	m3	336	336		167	5	153	9	2
Net Merch - All	m3/ha	34	34		17	1	15	1	C
Distribution	ક	100	100		50	2	46	3	1
Decay	용	5	5		2	18	7	5	11
Waste	8	1	1		0	9	2	1	(
Waste(billing)	8	1	1		0	14	2	1	C
Breakage	%	6	6		5	7	6	5	7
Total Cull (DWB)	%	11	11		7	35	14	11	18
Stems/Ha (Live & DP)		4.6	4.6		1.3	0.1	2.8	0.2	0.2
Avg DBH (Live & DP)	cm	83.0	83.0		104.7	87.0	74.0	64.2	45.3
Snags/Ha									
Avg Snag DBH	cm								
Gross Merch Vol/Tree	m3	8.32	8.32		13.71	7.69	6.47	5.13	1.58
Net Merch Vol/Tree	m3	7.39	7.39		12.75	5.03	5.55	4.55	1.29
Avg Weight Total Ht	m	50.9	50.9		58.9	46.3	44.3	40.4	26.1
Avg Weight Merch Ht	m	44.9	44.9		53.4	39.0	37.2	34.9	19.7
Avg 10.0 m Log Net	m3	2.08	2.08		2.53	1.39	1.86	1.34	0.70
Avg 10.0 m Log Gross	m3	2.20	2.20		2.59	1.92	2.03	1.42	0.79
Avg # of 10.0 m Logs	/Tree	3.78	3.78		5.30	4.00	3.19	3.60	2.00
Net Immature	ક								
Net 2nd Growth	8								
Average Slope	8	77							
Algorithm Grades %									
#1 Lum/#1 Prem	D	16	16		30		4		
#2 Lum/#1 Lum	F								
#2 Sawlog	H	21	21		13	50	29	36	
#3 Sawlog	I	42	42		44	19	38	37	
#4 Sawlog	J	4	4				8	7	
#4 Shingle	M					9			
#5 Utility	U	12	12		8	22	16	20	
#6 Utility	X	1	1				2		100
#7 Chipper	Y	4	4		5		3		
Statistical Summary									0.1.5
Coeff. of Variation	8	112.0	112.0		229.2	346.4	81.8	277.8	346.4
Two Standard Error	8	73.1	73.1		149.7	226.2	53.4	181.4	226.2
Number and Type of P.		MP =	12						
Number of Potential	rees	65							
Plots/Ha		1.2							
Cruised Trees/Plot		5.5							
Slope % Statistics			_		0000 00	_			

Grades: MOF Computerized

Computerized Decay

Computerized Waste

Computerized Breakage

Max=113, CV=32.9, Std Error of Mean=7.3, 2SE%=20.9 Min= 40,

*** 1 tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Leave Tree Report, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright© 1996-2015, Industrial Forestry Service Ltd.

Average Line Method

Project: TS2

ALBERNI VALLEY COM FOREST

Licence Number: K2D CP: PRE

LEAVE TREE REPORT

Block Summary

FIZ: B PSYU: Nootka

Region: 2 - West Coast District: 04 - South Island

Cruised by: CONTOUR FOREST CONSULTANTS IN

Compiled by: F Warren and Associates Ltd

03-May-2016 11:34:03AM Filename: TS2.ccp

BS- 3 , p4

Version: 2015.00 IFS build 5947

Grades: MOF Computerized Computerized Decay Computerized Waste Computerized Breakage

Net Area: Block: (M) - 001:TS2, Plots in Block: 12, TUs: [B RW: 0.1]

			a '.c	- 11	_	~		_	
TT- 171 T 1 1		Total	Conifer	Decid	F	С	Н	В	Y
Utilization Limits Min DBH cm (M)					17.5	17.5	17 5	17.5	17.5
- ()							17.5		
Stump Ht cm (M)					30.0	30.0	30.0	30.0	30.0
Top Dia cm (M)					15.0	15.0	15.0	15.0	15.0
Log Len m					10.0	10.0	10.0	10.0	10.0
Volume and Size Data									
Gross Merchantable	m3								
Net Merchantable	m3								
Net Merch - All	m3/ha								
Distribution	ક								
Decay	%								
Waste	%								
Waste(billing)	%								
Breakage	8								
Total Cull (DWB)	%								
Stems/Ha (Live & DP)	Ü								
Avg DBH (Live & DP)	cm								
Snags/Ha	Cili								
Avg Snag DBH	cm								
Gross Merch Vol/Tree	m3								
Net Merch Vol/Tree	m3								
Avg Weight Total Ht	m								
Avg Weight Merch Ht	m								
Avg 10.0 m Log Net	m3								
Avg 10.0 m Log Gross	m3								
Avg # of 10.0 m Logs									
Net Immature	8								
Net 2nd Growth	%								
Average Slope	%	77							
Algorithm Grades %									
#1 Lum/#1 Prem	D								
#2 Lum/#1 Lum	F								
#2 Sawlog	H								
#3 Sawlog	I								
#4 Sawlog	J								
#4 Shingle	M								
#5 Utility	U								
#6 Utility	X								
#7 Chipper	Y								
Statistical Summary									
Coeff. of Variation	8	112.0	112.0		229.2	346.4	81.8	277.8	346.4
Two Standard Error	8	73.1	73.1		149.7	226.2	53.4	181.4	226.2
Number and Type of Pi		MP =							
Number of Potential		65							
Plots/Ha		1.2							
Cruised Trees/Plot		5.5							
Slope % Statistics		5.5							
Min= 40 Max=113	CV=32 9	S+4 F	rror of Mea	n=7 3	2SE%=20 9				

Min= 40, Max=113, CV=32.9, Std Error of Mean=7.3, 2SE%=20.9

*** 1 tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Leave Tree Report, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright© 1996-2015, Industrial Forestry Service Ltd.

Average Line Method

Project: TS2

ALBERNI VALLEY COM FOREST

Licence Number: K2D CP: PRE

$\texttt{L} \ \texttt{E} \ \texttt{A} \ \texttt{V} \ \texttt{E} \qquad \texttt{T} \ \texttt{R} \ \texttt{E} \ \texttt{E} \qquad \texttt{R} \ \texttt{E} \ \texttt{P} \ \texttt{O} \ \texttt{R} \ \texttt{T}$

Type Stand Table (stems/ha)

FIZ: B

Grades: MOF Computerized Computerized Decay

Computerized Waste Computerized Breakage PSYU: Nootka Region: 2 - West Coast District: 04 - South Island Compiled by: F Warren and Associates Ltd Cruised by: CONTOUR FOREST CONSULTANTS IN

03-May-2016 11:34:03AM

Filename: TS2.ccp

TSTND- 1 , p5

Version: 2015.00 IFS build 5947

Type 1 (M):FdHw (BaCy), Plots in Type: 1, TUs: [A Block: 0.5]

TABE I (P	i) · ranw (i	Bacy,, Fiots	III IAbe.	1, 105.	[A BIOCI	0.5	1			
		F	C	H	В	Y	Total	DP	DU	LU
Utilizatio										
Min DBH	cm (M)	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
Stump Ht		30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0
Top Dia	cm (M)	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0
Log Len	m	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
DBH Class										
5										
10										
15										
20										
25										
30										
35										
40										
45 50										
55										
60										
65										
70										
75										
80										
85										
90 95										
100										
105										
110										
115										
120										
125										
130										
135 140										
145										
150										
175										
200										
225										
250										
275										
Total										
Dead P Dead U										
Live U										
			Aver	age DBH(c	m) at 5 1	Levels				
12.5 +				3 - (-						
17.5 +										
22.5 +										
27.5 +										
32.5 +										

*** 1 tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Leave Tree Report, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright@ 1996-2015, Industrial Forestry Service Ltd.

Average Line Method

Project: TS2

ALBERNI VALLEY COM FOREST

Licence Number: K2D CP: PRE

$\texttt{L} \ \texttt{E} \ \texttt{A} \ \texttt{V} \ \texttt{E} \qquad \texttt{T} \ \texttt{R} \ \texttt{E} \ \texttt{E} \qquad \texttt{R} \ \texttt{E} \ \texttt{P} \ \texttt{O} \ \texttt{R} \ \texttt{T}$

Type Stand Table (stems/ha)

FIZ: B

PSYU: Nootka

Grades: MOF Computerized Computerized Decay

Computerized Waste Region: 2 - West Coast Computerized Breakage District: 04 - South Island

03-May-2016 11:34:03AM Filename: TS2.ccp

Compiled by: F Warren and Associates Ltd Cruised by: CONTOUR FOREST CONSULTANTS IN

TSTND- 2 , p6

Version: 2015.00 IFS build 5947

Type 2 (M):FdHw(CyCwBa), Plots in Type: 2, TUs: [A Block : 1.7]

Win DBH cm (M) 17.5 17.5 17.5 17.5 17.5 17.5 17.5 17.5	TYPC Z	(M) · Pallw (Cyc	.wba/, IIoc.	, in type	. 2, 105.	[A DIOC	. 1.7	,			
Win DBH cm (M) 30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.			F	С	Н	В	Y	Total	DP	DU	LU
Stump Ht cm (M) 30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.											
Top Dia cm (M) 15.0 15.0 15.0 15.0 15.0 15.0 15.0 15.0											
Dob Len m 10.0 10.0 10.0 10.0 10.0 10.0 10.0 10									30.0		
DBH Class 5 10 15 20 25 30 35 40 445 55 60 65 70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 20 225 235 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +									15.0		
Class 5 10 15 15 20 20 25 25 30 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 + 4		ш	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
5 10 15 20 25 30 35 40 40 445 50 65 70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 175 200 225 235 275 Total Dead P Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
10 15 20 25 30 35 40 40 45 50 55 60 65 70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
20 25 30 35 40 40 45 50 55 60 65 70 77 77 78 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 17.5 + 17.5 + 22.5 + 17.5 + 22.5 + 27.5 +	10										
25 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 175 200 225 250 275 Total Pead P Dead U Live U Average DBH(cm) at 5 Levels 17.5 + 17.5 + 22.5 + 27.5 +											
30 35 40 45 50 55 60 65 70 75 80 85 99 100 105 110 115 120 125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 17.5 + 17.5 + 22.5 + 27.5 +											
35 40 45 50 55 60 65 70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 175 200 225 230 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
40 45 50 55 60 60 65 70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 17.5 + 17.5 + 22.5 + 27.5 +											
50 55 60 65 70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
55 60 65 70 75 80 85 90 95 1100 105 1110 115 120 125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
60 65 70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
655 770 775 80 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 17.5 +											
75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
90 95 100 105 110 115 120 125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
95 100 105 110 115 120 125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
100 105 110 115 120 125 130 135 140 145 150 175 200 225 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
105 110 115 120 125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +	95										
110 115 120 125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
115 120 125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
125 130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
130 135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
135 140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
140 145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
145 150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
150 175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
175 200 225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
225 250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
250 275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
275 Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
Total Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
Dead P Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
Dead U Live U Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
Average DBH(cm) at 5 Levels 12.5 + 17.5 + 22.5 + 27.5 +											
12.5 + 17.5 + 22.5 + 27.5 +	Live U										
17.5 + 22.5 + 27.5 +				Aver	age DBH(c	m) at 5 I	Levels				
22.5 + 27.5 +											
27.5 +											

*** 1 tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Leave Tree Report, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright@ 1996-2015, Industrial Forestry Service Ltd.

ALBERNI VALLEY COM FOREST

Licence Number: K2D CP: PRE

Average Line Method

Project: TS2

$\texttt{L} \ \texttt{E} \ \texttt{A} \ \texttt{V} \ \texttt{E} \qquad \texttt{T} \ \texttt{R} \ \texttt{E} \ \texttt{E} \qquad \texttt{R} \ \texttt{E} \ \texttt{P} \ \texttt{O} \ \texttt{R} \ \texttt{T}$

Type Stand Table (stems/ha)

Grades: MOF Computerized FIZ: B Computerized Decay

Computerized Waste Computerized Breakage

PSYU: Nootka Region: 2 - West Coast District: 04 - South Island Filename: TS2.ccp Compiled by: F Warren and Associates Ltd Cruised by: CONTOUR FOREST CONSULTANTS IN

TSTND- 3 , p7

Version: 2015.00 IFS build 5947

03-May-2016 11:34:03AM

Type 3	(M):HwFd(BaCyCw),	Plots	in Type:	9.	TUS:	[[4]	Treatment	Units	:	7.8	1
TAPC 3	(M) · MWI a (Dacycw),	LICCS	TIL TYPC.	ν,	105.	LUTT	II Ca ciliciic	CILLCD	•	7.0	

		_	_		_					
**************************************		F	С	H	В	Y	Total	DP	DU	LU
Utilization Min DBH	cm (M)	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
	cm (M)	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0
Top Dia	cm (M)	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0	15.0
Log Len	m (M)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
DBH	Ш	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Class										
5										
10										
15										
20										
25										
30										
35										
40				0.3			0.3			
45						0.2	0.2			
50				0.4	0.1		0.5			
55				0.8			0.8			
60										
65										
70		0.3		0.8	0.1		1.2			
75				0.1			0.1			
80				0.2			0.2			
85			0.1				0.1			
90		0.4		0.1			0.5			
95		0 0		0.1			0.1			
100		0.3		0 1			0.3			
105		0.3		0.1			0.1			
110 115		0.3		0.2			0.5 0.3			
120				0.3			0.3			
125		0.4					0.4			
130		0.1					0.1			
135										
140		0.1					0.1			
145										
150										
175										
200										
225										
250										
275										
Total		1.7	0.1	3.5	0.2	0.2	5.8			
Dead P										
Dead U										
Live U						_				
				age DBH(c						
12.5 +		104.7	87.0	74.0	64.2	45.3	83.0			
17.5 +		104.7	87.0	74.0	64.2	45.3	83.0			
22.5 +		104.7	87.0	74.0	64.2	45.3	83.0			
27.5 + 32.5 +		104.7 104.7	87.0 87.0	74.0 74.0	64.2 64.2	45.3 45.3	83.0 83.0			
34.3 T		104.7	0/.0	/4.0	04.2	43.3	03.0			

^{*** 1} tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Leave Tree Report, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright@ 1996-2015, Industrial Forestry Service Ltd.

ALBERNI VALLEY COM FOREST

Licence Number: K2D CP: PRE

Average Line Method

Project: TS2

$\texttt{L} \ \texttt{E} \ \texttt{A} \ \texttt{V} \ \texttt{E} \qquad \texttt{T} \ \texttt{R} \ \texttt{E} \ \texttt{E} \qquad \texttt{R} \ \texttt{E} \ \texttt{P} \ \texttt{O} \ \texttt{R} \ \texttt{T}$

Type Stand Table (stems/ha)

FIZ: B

Grades: MOF Computerized

Computerized Decay Computerized Waste Computerized Breakage PSYU: Nootka Region: 2 - West Coast District: 04 - South Island Filename: TS2.ccp Compiled by: F Warren and Associates Ltd Cruised by: CONTOUR FOREST CONSULTANTS IN

TSTND- 4 , p8

Version: 2015.00 IFS build 5947

03-May-2016 11:34:03AM

Trmo 2	/M) · U E-3	(BaCyCw)	Dlota	in Time:	0 TIIG •	Γ 7\	Dlook	• 7 7	1
Type 3	(M) · HWFO	(Bacycw),	PIOLS	Tu Type.	9, IUS.	L A	BIOCK	. / . /	

-71 ()		,,		,			•			
		F	С	H	В	Y	Total	DP	DU	LU
Utilization										
	m (M)	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
Stump Ht c		30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0
_	m (M)	15.0 10.0	15.0	15.0 10.0	15.0 10.0	15.0 10.0	15.0 10.0	15.0 10.0	15.0 10.0	15.0
Log Len DBH	m	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Class										
5										
10										
15										
20										
25										
30										
35										
40				0.3		0 0	0.3			
45 50				0.4	0.1	0.2	0.2			
55				0.4	0.1		0.8			
60				0.0			0.0			
65										
70		0.3		0.8	0.1		1.2			
75				0.1			0.1			
80				0.2			0.2			
85			0.1				0.1			
90		0.4		0.1			0.5			
95		0 2		0.1			0.1			
100 105		0.3		0.1			0.3 0.1			
110		0.3		0.1			0.5			
115		0.5		0.3			0.3			
120				0.5			0.5			
125		0.4					0.4			
130										
135										
140		0.1					0.1			
145										
150										
175 200										
225										
250										
275										
Total		1.7	0.1	3.6	0.2	0.2	5.9			
Dead P										
Dead U										
Live U						_				
					m) at 5 I					
12.5 +		104.7	87.0	74.0	64.2	45.3	83.0			
17.5 +		104.7	87.0	74.0	64.2	45.3	83.0			
22.5 + 27.5 +		104.7 104.7	87.0 87.0	74.0 74.0	64.2 64.2	45.3 45.3	83.0 83.0			
32.5 +		104.7	87.0	74.0	64.2	45.3	83.0			
J2.J '		101.7	07.0	, 1.0	01.2	13.3	03.0			

*** 1 tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Leave Tree Report, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright@ 1996-2015, Industrial Forestry Service Ltd.

Average Line Method

Project: TS2

ALBERNI VALLEY COM FOREST

Licence Number: K2D CP: PRE

LEAVE TREE REPORT

Type Stand Table (stems/ha)

FIZ: B

Grades: MOF Computerized

Computerized Decay Computerized Waste Computerized Breakage PSYU: Nootka Region: 2 - West Co

Region: 2 - West Coast District: 04 - South Island 03-May-2016 11:34:03AM
Filename: TS2.ccp
Compiled by: F Warren and Associates Ltd

TSTND- 5 , p9

Cruised by: CONTOUR FOREST CONSULTANTS IN Version: 2015.00 IFS build 5947

```
Type 3 (M):HwFd(BaCyCw), Plots in Type: 9, TUs: [ B RW : 0.1 ]
```

Type 3 (I	1) · HWF a (bac	.ycw/, 110c.	, ill lypc	. , 105.	[D KW ·	0.1				
		F	С	Н	В	Y	Total	DP	DU	LU
Utilizatio		45.5								
Min DBH	cm (M)	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
Stump Ht Top Dia	cm (M)	30.0 15.0								
Log Len	m (M)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
DBH	111	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Class										
5										
10										
15										
20 25										
30										
35										
40										
45										
50										
55 60										
65										
70										
75										
80										
85										
90 95										
100										
105										
110										
115										
120										
125 130										
135										
140										
145										
150										
175										
200 225										
250										
275										
Total										
Dead P										
Dead U										
Live U			7	DDII/	\ a+ F T	1				
12.5 +			Aver	age DBH(C	m) at 5 I	TEAGTR				
17.5 +										
22.5 +										
27.5 +										
32.5 +										

*** 1 tree(s) changed to tree class 6:because only log was less then 3.00 m *** FLAGS: Leave Tree Report, Normal Cruise, All Trees Compiled, Measure Plots Only, Damage, CruiseComp Copyright® 1996-2015, Industrial Forestry Service Ltd.



File: 11400-25, R18553, Amendment #13

Alberni Valley Community Forest Corporation 7500 Airport Road Port Alberni, British Columbia V9Y 8Y9

Dear Sir/Madam:

Reference is made to your application dated February 18, 2016, for an amendment of Road Permit (RP) No. R18553 within Alberni Valley Community Forest Licence K2D.

Pursuant to paragraph 1.01 and 2.01 of RP No. R18553, the roads identified in the list below, and the attached map shall form an integral part of the document for RP No. R18553 and should be attached thereto.

This amendment pertains to the construction, maintenance and use of the following roads within the Alberni Valley Community Forest Corporation 2011 to 2016 Forest Stewardship Plan approved June 6, 2011:

Licensee	Sec. Designation	Station(from)	Station(to)
Road Name	on Exhibit A Map		
TA568	TA568	2+209	3+099
TA568G	TA568G	0+000	0+063
TA568H	TA568H	0+000	0+099
TA568J	TA568J	0+000	0+888

All operations are to conform to the *Forest and Range Practices Act*. The Forest Road Engineering Guidebook may be used to assist achieving compliance with the Act.

	
Attachment: Exhibit A Map (ESF 1492993)	

Ministry of Forests, Lands and Natural Resource Operations

Yours truly,

South Island Natural Resource District

Location: 4885 Cherry Creek Road Port Alberni BC Mailing Address: 4885 Cherry Creek Road Port Alberni BC V9Y 8E9

Tel: (250) 731-3000 Fax: (250) 731-3010




EXHIBIT A



MAP OF: R18553 Amendment #13 (shown in bold black)					
FOREST REGION : RWC FOREST DISTRICT : DSI	TSA : LAND DISTRICT : CLAYOQUOT DISTRICT	PULPWOOD AGREEMENT :	MGT UNIT TYPE : COMMUNITY FOREST MGT UNIT NO :		
ESF SUBMISSION ID : 1492993 BCGS MAPSHEET NO : 92F.024	SCALE: 1:20000 at A Size Length (Km): 4.148	UTM : 10 NAD : NAD83	DRAWN BY : FTA DATE : Feb 19, 2016		





Legend Tenure Application Tenure Road Application Retired Tenure Road P of C P of T Tenure Feature Range TFL **Provincial Forest** Forest Service Road Highway Municipal Road Non Status Road Recreation Trails Road Permit SUP Road Right of Way Schedule B CP Road Mineral Tenure Points Cities Waterbodies River/Stream Coastline / Island TA568G (Length: 0.0632 Km, R/W: 75 m) PofC UTM10 329965, 5460967 PofT UTM10 329942, 5461026 TA568H (Length: 0.0985 Km, R/W: 75 m PofC UTM10 330409, 5460500 PofT UTM10 330473, 5460573

Poli UTM/10 3204/3, 34009/37 TA568 (Length: 3.0988 Km, R/W: 75 m) PofC UTM/10 329419, 5461533 PofT UTM/10 330218, 5460630 TA568J (Length: 0.8879 Km, R/W: 75 m) PofC UTM/10 330218, 5460630 PofT UTM/10 330519, 5460405



TERRAIN STABILITY FIELD ASSESSMENT Cutblock TS2

SUMMARY

Cutblock

Apart from the two areas mentioned below, the proposed cutblock has a *Very Low to Low* potential for post-harvest landslides.

Polygon 3 of Unit A has a *Moderate* potential for landslides and *High* for rockfall. If a slide does occur, it would likely stop in Stream 4.

Polygon 3 of Unit B has a *Moderate* potential for landslides and *High* for rockfall. If a landslide does occur, it would likely dewater quickly and stop at the built road TA568D.

Road TA568 Renamed TA568J on Feb17,2016

From Stn. 032 to Stn. 130, from Stn. 317 to Stn. 337, and from Stn. 395 to Stn. 420, Full Bench Endhaul will reduce the potential for Fillslope failures to *Low*. Cutslope Angle should be 3:1 in competent bedrock.

Safety Hazards

Polygon 3 of Unit A and Polygons 2 and 3 of Unit B have a *High* potential for rockfall from within and upslope of the polygon.

Terrain Risk Associated with Windthrow

If post-harvest windthrow occurs along Streams 3 and 5, it would result in trees sliding into the streams, introducing small to possibly moderate amounts of sediment. A debris flow could occur in Stream 3 and this could travel into the

clearcut downstream of the proposed cutblock. If windthrow occurs along the eastern edge of Unit B, it would likely result in rockfall and could possibly contribute to landslide initiation. Rockfall and landslides could reach TA568D if these events occur along the northern portion of this boundary segment.

INTRODUCTION

Geoforestry Consulting was retained by Meridian Forest Services Ltd. (Meridian) to assess the terrain-related hazards for the proposed Cutblock TS2 in the Taylor River drainage system. I inspected the area on August September 21st, 2015, accompanied by Darin Brown and Donna Underwood, R.P.F. of Meridian. Approximately 5 hours were spent on site. It was sunny and hot.

Information reviewed prior to my field assessment consisted of:

- 1:5,000-scale contour map showing boundary locations.
- Aerial photographs were not available.
- Google Earth 3D Images
- 1:5,000 Terrain Map

The proposed cutblock was ribboned and traversed at the time of the assessment. The cutblock will be harvested conventionally and with helicopter yarding.

Location

The proposed cutblock is located a short distance to the west of the western end of Sproat Lake. It is situated on north-facing slopes overlooking several tributaries to Sutton Creek.

Access to the area is via the TA568 road systems.

General Description of Cutblock

The proposed cutblock consists of three separate units, which for the purposes of this report are designated Units A through C. Unit A is located in the southern portion of the cutblock and has gullies on either side of the layout. The road TA568 will be extended into Unit A.

Unit B is located a short distance north of Unit A across Stream 3. The ground in this area slopes to the north and west towards TA568D. This area will be harvested from the built road and partially by helicopter yarding.

Unit C is a small area located in the northwestern portion of the development area. A short spur road will be constructed into this area.

Bedrock Geology

Bedrock in the area consists of the Triassic-aged Karmutsen Volcanics. Volcanic bedrock is exposed throughout the development area. The bedrock is regionally faulted and this has produced a strong step-bench topography with the axis of the features oriented to the northwest. Streams 3, 4, and 5 likely flow along bedrock faults.

Steep bedrock bluffs are weathering to produce large amounts of coarse colluvium in Polygon 3 of Unit A and in Polygons 2 and 3 of Unit B.

Surficial Geology

Soils are generally thin throughout the proposed cutblock. They have a silty-rubbly texture and are mainly derived from weathered bedrock. These soils are generally moderately well to well drained.

There are some pockets of sandy-diamictic till exposed along the cutslope of TA568D. Although there is little evidence of till within the cutblock, there could be pockets. Sand-based till generally weathers to produce moderately well to well drained soils.

Downslope Resources

The proposed cutblock is located within the Sproat Lake Community Watershed. As far as I am aware, there are no fish-bearing streams located within the proposed cutblocks but the streams within are mapped as S4 and Streams 3 and 5 are mapped as S3.

AVCF - Meridian Page 4 October, 2015

From most areas within the proposed cutblocks, the potential for landslide runout is considered short due to coarse materials and the step-bench topography; benches are locally broad enough to stop landslides.

Longer runout is possible from some of the ground within the northern portion of Unit A, in the eastern portion of Unit B, and the northern portion of Unit C.

Existing Landslides

The surrounding area was inspected for evidence of existing landslides on the air photos, on the drive and flight to the cutblock, and during the ground inspection. Determination of the cause of the landslides outside of the cutblock is important because the conditions present in the initiation zone can be compared to the conditions within the proposed cutblock and/or road alignment. Should similar conditions be found to exist, thorough field observations should be carried out to ensure stability.

I am not aware of any significant open-slope natural or logging-related landslides located within or adjacent to the proposed cutblock. There are slope movement indicators on steep ground located within the proposed cutblock and these areas have a moderate potential for post-harvest landslides.

Rockfall from steep fractured bedrock bluffs exists within and adjacent to some areas of the proposed cutblock.

TERRAIN STABILITY HAZARD RATINGS

A terrain stability hazard rating is the estimated potential for landslide initiation in a given area after road building and/or logging. Determination of a hazard rating is based primarily on the following:

- Hillslope gradient
- Topography
- Surficial material type, texture, and structure
- Derived soils, their texture and drainage
- Bedrock geology of the area
- Vegetation, primarily wet-site indicators
- Evidence of previous landslides or indications of active instability
- Experience in similar terrain with similar geological conditions
- Proposed yarding methods and road location and design

- Potential changes to the natural hillslope drainage pattern
- > The effects of root decay

The following are some reference reports that explain in part how I arrive at the hazard ratings presented in this report.

- The report "Terrain Stability Management Strategy for Rennell Sound" by this investigator, May, 2005
- > The report "Some Relationships between Bedrock, Shallow Landslides, and Forest Practices", June, 2003, by this investigator
- WFP Terrain Risk Management Strategy, March 2012

A four-class system (Very Low, Low, Moderate, or High) is used to describe the terrain stability hazard rating of a given area or road section. The criteria used for this classification system can be found in the attached Appendix A.

Consequence refers to the anticipated damage caused by a potential landslide. Damage is quantified by first estimating the composition, size, and runout distances of slides. Then the following downslope entities are considered:

- Human safety
- The potential to damage infrastructure such as roads or buildings.
- environmentally sensitive receptors such as fish-bearing drainages
- Loss of resource and site degradation

The potential runout distances for slides and their downslope impacts are described in Table 1.

FIELD OBSERVATIONS AND HAZARD MITIGATION OPTIONS

Terrain Hazards Related to Harvesting

The following Table 1 includes observations of the geological conditions and hillslope gradient and topography within an area of the opening. Based on the observations, an area has been assigned a terrain stability hazard rating. I have mapped out areas of homogenous terrain conditions and hazard ratings into polygons, which are shown on the accompanying map of the opening. The

delineation of each polygon is completed in the field and is an approximation, based on tying into falling corners and topographic maps.

For each polygon, should a slide be triggered (even Low hazard polygons can have slides), the downslope impacts of a slide, including anticipated runout distance and interceptors are described.

Terrain Hazards Related to Road Construction

The following Table 2 includes observations of the geological conditions and hillslope gradient and topography along a specified segment of the proposed road alignment. Based on the observations, each specified road segment has been assigned a post-construction hazard rating for conventional construction techniques. Each specified road segment is based on having homogenous terrain conditions and hazard ratings and is delineated in the field.

For road segments that have a higher than Low post-construction failure rating, alternative construction options and the post-construction failure ratings are provided. The hazard ratings provided in this table include the potential instability from road fillslopes and cutslopes and road drainage

Page 6

Table 1. Geological Observations, Terrain Hazard and Consequences for Polygons in Cutblock TS2

Polygon		Geological	Hillslope Gradient and		Consequence of	Remarks
, 5	Description	Conditions	Topography	Stability Hazard	a Landslide	
Unit A						
1	Polygon 1 is located along the northern edge of Unit A.	Thin moderately well drained soils derived mainly from weathered bedrock.	45 to 70%.	Low	A landslide would likely be small and travel less than 100 m.	
2	This polygon occupies the majority of Unit A.	Generally thin soils derived from weathered bedrock but with some deeper pockets likely derived from till. Scattered bedrock outcrops with up to over 15 m vertical relief.	Variable topography with some broad gently-sloping benches and other 30 m sections of up to 75%.	Low and Very Low	A landslide would likely be very small to small and stop in this polygon. From some areas in the downslope portion of the polygon long runout of over 100 m is possible.	
3	Polygon 3 is located in the eastern portion of the polygon along Stream 4. This stream flows along what is likely a bedrock fault; the concave feature is larger than could have been eroded by this stream.	Thin colluvium and fractured bedrock outcrops to over 8 m high.	Generally steep at over 70% and up to over 80%.	Moderate	A landslide would likely be small and would probably stop at the toe of the slope within Stream 4. A slide event might be able to travel down Stream 4 to Stream 3 but would have to travel parallel to the stream to have enough momentum once it hits the stream to travel down it.	

Polygon 4	General Polygon Description This polygon is located along the eastern edge of Unit A. The ground in this polygon slopes towards Polygons 2 and 3.	Geological Conditions Moderately well drained soils derived from weathered bedrock and colluvium. Soils are wetter around FC25 to FC26.	Hillslope Gradient and Topography 45 to 70% near FC25. A snow avalanche may have impacted this area. There is a rock bluff estimated to be 40 to 50 m high just south of FC25 to FC26. Some benched	Stability Hazard Low	Consequence of a Landslide A landslide would likely be small and would probably stop in Polygon 2.	Remarks
			ground between FC26 and FC30.			
Unit B						
1	Polygon 1 is located in the southwestern portion of Unit B.	Some coarse colluvium along upslope edge.	Generally 15 to 45% with some short steeper sections on the downslope edge.	Low and Very Low	A landslide would likely be very small or smaller and would stop in this polygon. If a slide goes out of this polygon, it would likely reach the built road below.	
2	This polygon is located in the southeastern portion of Unit B. The ground in this polygon slopes towards Polygon 1.	Abundant coarse colluvium. Steep bedrock bluffs just upslope of the falling boundary.	65 to 75%	Low for Landslides, High for rockfall.	A landslide would likely be very small and would stop in this polygon or in Polygon 1.	Workers should be made aware of the hazard for rockfall from within and upslope of this polygon.
3	Polygon 3 is located in the northern portion of Unit B. The ground in this polygon slopes towards the built road TA568D.	Abundant bedrock as well as colluvium and fine soil pockets. Actively raveling and rockfall from within most of the polygon.	70 to over 85% with irregular topography.	Moderate	A landslide would likely be small to moderate in size and would likely dewater quickly and stop at TA568D.	

Polygon	General Polygon Description	Geological Conditions	Hillslope Gradient and Topography	Terrain Stability Hazard	Consequence of a Landslide	Remarks
Unit C						
1	Polygon 1 occupies the majority of Unit C.	Moderately well drained soils derived from weathered bedrock and some colluvium. Bedrock outcrops around this polygon.	Generally about 45 to 70% with 15 m of 70 to 85%.	Low	A landslide would likely be small but could travel over 100 m downslope, possibly to the built road.	
2	This small polygon is located in the upslope or southern portion of Unit C.	Thin folisols.	Less than 25%.	Very Low	N/a.	

Table 2. Hazard Rating and Consequences for Construction Options – TA568 & Spurs

Road Section	Hillslope Gradient and Topography	Geological Conditions	Construction Options	Post Construction Landslide Hazard Cutslope/ Fillslope	Road Drainage Hazard	Consequence of a Slide	Remarks
TA568				_			
Stn. 000 – Stn. 032	The alignment cuts up onto the cutslope of the built road.	Shallow colluvium.	Conventional	Low/ Low	Low	A landslide would be very small or smaller and stop on the built road.	

Road Section	Hillslope Gradient and Topography	Geological Conditions	Construction Options	Post Construction Landslide Hazard Cutslope/ Fillslope	Road Drainage Hazard	Consequence of a Slide	Remarks
Stn. 032 – Stn. 130	+65 to 80%, -55 to 70%. Stream 4B flows in a concave feature at about 15 to 20 m wide by 3 m deep.	Thin soils and bedrock. Many wetsite plants.	Conventional	Low/ Moderate	Low	A landslide would likely be small and would probably travel less than 50 m due to close proximity to benches (below centerline).	
			Full Bench Endhaul. Cutslope Angle 3:1 in Competent Bedrock.	Low/ Low	Low	Little material available to slide	This option reduces the potential for Fillslope failures to Low.
Stn. 130 – Stn. 300	Generally in the range of +/-45 to 55%. Some steeper sections on bedrock outcrops.	Generally thin soils and bedrock outcrops.	Conventional	Low/ Low	Low	A landslide would likely be very small and would probably stop within about 15 m on small benches. If it travels past the benches, it could travel about 50 to 75 m to the lower road.	

Road Section	Hillslope Gradient and Topography	Geological Conditions	Construction Options	Post Construction Landslide Hazard Cutslope/ Fillslope	Road Drainage Hazard	Consequence of a Slide	Remarks
Stn. 300 – Stn. 317	-40% for 2 m and -15 to 25% for 10 m. 4 m high bedrock outcrop just upslope of centerline.	Thin soils and bedrock outcrops.	Conventional	Low/ Low	Low	A landslide would likely be very small but could potentially travel over 100 m downslope if it travels past the small bench.	
Stn. 317 – Stn. 337	The alignment cuts up through bedrock that is approximately 4 m high.	Mainly bedrock.	Conventional Full Bench	Low/ Moderate Low/ Low	Low	A landslide could be small to moderate in size and could travel over 100 m downslope. Little material	This option
			Endhaul. Cutslope Angle 3:1 in Competent Bedrock.			available to slide	reduces the potential for Fillslope failures to Low.
Stn. 337 – Stn. 395	The alignment crosses irregular rocky ground. Locally the downslope gradient is up to 60% for about 6 m but there is 15 m of less than 30% ground downslope of that.	Thin soils and bedrock outcrops. One bedrock outcrop is 8 to 10 m high and located just upslope of centerline.	Conventional	Low/ Low	Low	A landslide could be small to moderate in size and could travel over 100 m downslope if it travels past the bench located just below centerline.	

Road Section	Hillslope Gradient and Topography	Geological Conditions	Construction Options	Post Construction Landslide Hazard Cutslope/ Fillslope	Road Drainage Hazard	Consequence of a Slide	Remarks
Stn. 395 – Stn. 420	Up to -60% for 6 to 8 m with steep ground downslope of that.	Thin soils and bedrock.	Conventional	Low/ Moderat e	Low	A landslide could be small to moderate in size and could travel over 100 m downslope.	
			Full Bench Endhaul. Cutslope Angle 3:1 in Competent Bedrock.	Low/ Low	Low	Little material available to slide	This option reduces the potential for Fillslope failures to Low.
Stn. 420 – Stn. 587	Generally less than 25%.	Thin folisols.	Conventional	Very Low/ Very Low	Low	N/a.	
Stn. 587 – Stn. 640	The alignment is located near the toe of steeper ground. +55 to 75% for up to 30 m40 to 50 for less than 5 m with a 15 m gently-sloping bench below that.	Moderately well to well drained thin soils.	Conventional	Low/ Low	Low	A landslide would likely be very small and travel less than 20 m.	
Stn. 640 – Stn. 712	Generally +/-40 to 50%. Some small benches of less than 25%.	Moderately well to well drained thin soils.	Conventional	Low/ Low	Low	A landslide would likely be small initially but could potentially travel several hundred meters downslope.	

Road Section	Hillslope Gradient and Topography	Geological Conditions	Construction Options	Post Construction Landslide Hazard Cutslope/ Fillslope	Road Drainage Hazard	Consequence of a Slide	Remarks
Stn. 712 – Stn. 750	The alignment is located on the outer sidewall of the Stream 4 system. The ground is less than 60% but will require a steep road grade.	Moderately well to well drained silty-rubbly soils derived mainly from weathered bedrock.	Conventional	Low/ Low	Low	A landslide would likely be small and travel less than 50 m.	
Stn. 750 – Stn. 852	15 to 50%. 2 to 3 m drop below centerline between Stn. 810 and Stn. 820. Gently- sloping below that.	Moderately well to well drained soils derived mainly from weathered bedrock.	Conventional	Low and Very Low for both Cutslope and Fillslope.	Low	A landslide could potentially travel well over 100 m downslope.	
Stn. 852 – Stn. 888	Less than 25%.	Moderately well drained thin silty- rubbly soils derived mainly from weathered bedrock.	Conventional	Very Low/ Very Low	Low	N/a.	
TA568E							
Stn. 000 – Stn. 050	Generally +/-40 to 50%.	Moderately well drained thin soils.	Conventional	Low/ Low	Low	A landslide would likely be small initially but could potentially travel over 100 m downslope.	
Stn. 050 – Stn. 099	Less than 25%.	Moderately well drained thin soils derived mainly from weathered bedrock.	Conventional	Very Low/ Very Low	Low	N/a.	
TA568F							
Stn. 000 – Stn. 063	Generally less than 25%.	Moderately well to well drained thin folisols.	Conventional	Very Low/ Very Low	Low	N/a.	

GULLIES, GULLY-LIKE FEATURES, and FANS

This section lists and describes significant gullies, gully-like terrain, and fans within and adjacent to the proposed cutblock. The purpose of this section is to alert foresters and managers to these features in order to facilitate management of windthrow and sediment.

The three streams described below are likely all flowing along bedrock faults. Therefore the depth of the features is not represented just by erosion.

Stream 3

Near FC27 the stream flows in a gully that is estimated at over 100 m wide. The eastern sidewall is about 75 to 100 m high and contains abundant bedrock and it is very steep. The western sidewall is about 20 m high and very steep. The active channel is over 5 m wide and it is transporting material to boulder size.

Near FC17 the gully is about 25 m wide by 6 to 15 m deep with steep rocky sidewalls. The active channel is about 6 to 8 m wide and it is transporting material to boulder size over a stepped gradient. The channel substrate comprises mainly bedrock.

Stream 4

Near FC31 the stream flows in a gully-like feature that is about 15 to 20 m wide by 8 to 10 m deep with steep rocky sidewalls. The bedrock along the stream is oxidized. The active channel is about 1.25 m wide.

Stream 5

Near FC21 the stream flows in a gully that is about 30 m wide. The northern sidewall is about 7 to 10 m high; the southern sidewall about 15 to 20 m high. The sidewalls and substrate comprise mainly bedrock. The active channel is over 5 m wide and it is transporting material to boulder size. A short distance upstream the feature is about 10 to 20 m wide by 3 to 8 m deep – it does vary in size and depth upstream.

Near FC24 the feature is about 30 m wide with a 4 to 5 m northern sidewall and 15 m high southern sidewall.

TERRAIN RISK ASSOCIATED WITH WINDTHROW

This section deals with the anticipated terrain hazard and consequence should windthrow occur along an edge of the cutblock following harvesting. This section is not a windthrow hazard assessment; it is intended to be used by the silvicultural prescription writer, layout engineers, and managers as a guide for possible edge treatments such as topping or pruning. Only those edges that I consider to have significant terrain risk associated with windthrow are included below. If the layout crew determines that the hazard of windthrow is low, then treatment of the edge would likely not be required.

Segment 1; Stream 3

This stream is described above in the Gullies section of the report. If post-harvest windthrow occurs along this stream, trees would slide into the stream, introducing small to possibly moderate amounts of sediment. A debris flow could occur and could travel into the existing clearcut downslope of the proposed cutblock.

Segment 2: Stream 5

This stream is described above in the Gullies section of the report. If postharvest windthrow occurs along this stream, trees would slide into the stream, introducing small to possibly moderate amounts of sediment. A debris flow is unlikely to occur.

Segment 3: Steep Rocky Ground Eastern Edge Unit B

The falling boundary is located against steep fractured rocky ground. If post-harvest windthrow occurs along this edge, it would likely result in rockfall and could possibly contribute to landslide initiation. Rockfall and landslides could reach TA568D if these events occur along the northern portion of this boundary segment.

CONCLUSIONS

The proposed cutblock is mostly located on stable ground but there are some steep and potentially unstable areas due in part to regional bedrock faulting. Polygon 3 of Unit A has a moderate potential for landslides and high for rockfall. If a slide does occur, it would likely stop in Stream 4. Polygon 3 of Unit B has a moderate potential for landslides and high for rockfall. If a landslide does occur, it would likely dewater quickly and stop at the built road TA568D.

For road TA568, from Stn. 032 to Stn. 130, from Stn. 317 to Stn. 337, and from Stn. 395 to Stn. 420, Full Bench Endhaul will reduce the potential for Fillslope failures to Low. Cutslope Angle should be 3:1 in competent bedrock.

Polygon 3 of Unit A and Polygons 2 and 3 of Unit B have a high potential for rockfall from within and upslope of the polygon.

If post-harvest windthrow occurs along Streams 3 and 5, it would result in trees sliding into the streams, introducing small to possibly moderate amounts of sediment. A debris flow could occur in Stream 3 and this could travel into the clearcut downstream of the proposed cutblock. If windthrow occurs along the eastern edge of Unit B, it would likely result in rockfall and could possibly contribute to landslide initiation. Rockfall and landslides could reach TA568D if these events occur along the northern portion of this boundary segment.

LIMIT OF LIABILITY

This report provides an assessment of the potential for terrain instability following timber harvesting in accordance with the harvesting plans disclosed to Geoforestry Consulting.

The evaluation of the hazards contained within this report is based upon limited visual inspection of surface expression, road cuts, slope failures, gullies, and/or shallow soil pits in the proposed harvesting area along with our experience in similar terrain. It represents our professional opinion of the hazards in the area assessed. However, it is not intended to be a guarantee or warranty of the actual conditions or hazards existing in the area. No other surface or subsurface investigation was performed. Accordingly, assessment of the potential for deep-seated bedrock failures is beyond the scope of this report.

Predicting the location or distribution of underground water conduits, zones of soft bedrock, or developing failure plains is beyond the scope of this assessment if they are not expressed on the ground surface in terms of plant growth, surface water flow, or topographic features (draws, bowls, or channels). It is possible during heavy rainfall events that springs will develop in areas where there is no surface expression of existing springs. If a spring develops during a heavy rainstorm, it could trigger a landslide depending upon its location.

Geological conditions other than those indicated in this report may exist in the area assessed. If such conditions are observed, Geoforestry Consulting should be immediately contacted so that this report may be reviewed and amended accordingly.

This report pertains to the circumstances and conditions which apply to the specific harvesting plans disclosed and it can not be reasonably used for any purpose except in order to complete the specific harvesting plans disclosed and by government agencies regulating these specific harvesting activities. It is not reasonable for any third party to rely upon this or any of the observations, opinions or conclusions contained herein and any reliance on or decisions made by third parties based upon this report remains the responsibility of such third parties. Geoforestry Consulting accepts no responsibility for damages, if any, suffered by any third party as a result of any reliance upon this report.

Prepared by:

BRITISH 30 ZOTS

Jack Whittles, M.Sc., P.Geo.

PESSION



APPENDIX A

(From Western Forest Products Terrain Risk Management Strategy 2012)

Table 1: Terrain Hazard Definitions

нісн	>5 failures per 100 ha logged on steep
	terrain.
MODERATE	3-5 failures per 100 ha logged on steep
	terrain.
LOW	1-<3 failures per 100 ha logged on
	steep terrain.
VERY LOW	<1 failure per 100 ha logged on steep
	terrain.

- Failure = 0.05 ha event (smallest inventoried and smallest visible on airphotos)
- Steep terrain = Class IV/V; Es1/Es2; P/U; >60%
- Terrain to be evaluated with a 1 in 15 year storm event in mind (100 mm in 24 hrs)

Table 2: Landslide Size

1	0.05 – 0.1 ha	Very Small
2	<0.1 – 0.25 ha	Small
3	<0.25 – 0.5 ha	Medium
4	<0.5 – 1 ha	Large
5	>1 ha	Very Large

Table 3: Consequence Definitions

	•
HIGH	Landslide would directly enter fish stream,
	fish lake, or marine waters, or water intake
	for domestic consumption, or jeopardizes
	lives of the public, or impact major public
	infrastructure, or other property owner.
	Landslide would enter nonfish stream
	within 500 m of fish bearing waters.
MODERATE	Landslide would enter nonfish stream more
	than 500 m from fish bearing waters, OR
	there is a runout slope of <20% for <100 m
	below landslide to fish bearing waters or
	intake to a public area, or other property
	owner.
LOW	• There is a runout slope of <20% for >200 m
	below landslide. Some suspended
	sediment and small woody debris may
	reach fish habitat/intake, or public area, or
	other property owner.
VERY LOW	• There is a runout slope of <20% for >200 m
	below landslide. Slide material is unlikely
	· I
	to reach stream/intake at time of event or
	to reach stream/intake at time of event or
	to reach stream/intake at time of event or transport to stream. A landslide would not

